

ARCW33APH5B201A Card reader, OSDP, standard



- ▶ 13.56 MHz proximity compatible with access controllers with RS485 interface
- ▶ IP65 rated for indoor and outdoor use
- ▶ Supports MIFARE Classic (CSN), MIFARE DESFire EV1, EV2 and EV3 (CSN)
- ▶ OSDP V2 Secure Channel support

The STid reader has three different form factors: it is pre-configured and programmed, ready to use and available in black color. It can be surface-mounted and an optional mounting box can be used.

This reader is suitable for the US Gang Box, and it complies with the European standard as well.

To provide a wide range of solutions, the reader is fully compatible with the Bosch Access management portfolio, including not only the Management Software Systems (Access Management System - AMS - and Building Integration System - BIS), the Access Modular Controller (AMC2), but also the entire MIFARE credential portfolio.

The STid reader is very simple to use, and provides clear feedback to the user during operation, due to the LED and beeper.

Because the reader is IP65 and IK10 rated, it is optimally suited for outdoor environments, and provides the highest level of resistance against vandalism.

Installation/configuration notes

The terminal interface of the reader is so easy to install. A variety of card data formats are supported based on the card technology, including 32bit and 56bit formats. Due to the integrated audio, the cardholder can very easily distinguish between access granted and access denied.

Parts included

Quantity	Component
1	Reader module
1	Installation note

Quantity	Component
2	Screws
1	Locking bar
1	Condenser
1	Resistor

Technical specifications

Mechanical

Dimensions (H x W x D) (mm)	106.64 mm x 80 mm x 25.70 mm
Dimensions (H x W x D) (in)	4.21 in x 3.15 in x 1.02 in
Color	Black
Material	Plastic
Mounting type	Surface-mounted
Weight (g)	122 g
Weight (lb)	0.268 lb

Environmental

Operating temperature (°C)	-30 °C – 70 °C
Operating temperature (°F)	-22 °F – 158 °F
Usage	Indoor; Outdoor
IP rating	IP65

Impact protection	IK10
Electrical	
Operating voltage (VDC)	7 VDC – 28 VDC
Operation	
Audible indication	Yes
Credential type	Cards/keyfobs/tokens
Keypad	No
Optical indication	LED
Software compatibility	Building Integration System; Access Management System
Wireless transmission frequency	13.56 MHz
Reading format	ISO14443A CSN 32 bit; ISO14443A CSN 56 bit; MIFARE DESFire EV2; MIFARE DESFire EV1; MIFARE Classic
Read range (cm)	0 cm – 8 cm
Read range (in)	0 in – 3.15 in
Connectivity	
Reader interfaces	RS485
System integration	
Protocols / standards	OSDP

KIT-SPACER-ARC-NO Wallmount box, ARC, black
 Wallmount box for the standard STid readers with and without keypad, black.
 Order number **KIT-SPACER-ARC-NO | F.01U.410.592**

Ordering information

ARCW33APH5B201A Card reader, OSDP, standard
 Standard OSDP reader for MIFARE Classic, MIFARE EV1, EV2 and EV3, black, IP65 rated for indoor and outdoor.
 Order number **ARCW33APH5B201A | F.01U.410.590**

Accessories

KITBCBOSCH20 Address config card set for ARC OSDP
 Set of eight cards for the configuration of the reader address 1 to 8.
 Order number **KITBCBOSCH20 | F.01U.412.888**

Represented by:

Europe, Middle East, Africa:
 Bosch Security Systems B.V.
 P.O. Box 80002
 5600 JB Eindhoven, The Netherlands
 Phone: + 31 40 2577 284
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Germany:
 Bosch Sicherheitssysteme GmbH
 Robert-Bosch-Ring 5
 85630 Grasbrunn
 Tel.: +49 (0)89 6290 0
 Fax: +49 (0)89 6290 1020
de.securitysystems@bosch.com
www.boschsecurity.com

North America:
 Bosch Security Systems, LLC
 130 Perinton Parkway
 Fairport, New York, 14450, USA
 Phone: +1 800 289 0096
 Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.com

Asia-Pacific:
 Robert Bosch (SEA) Pte Ltd, Security Systems
 11 Bishan Street 21
 Singapore 573943
 Phone: +65 6571 2808
 Fax: +65 6571 2699
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com