

CCS 900 Ultra System

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Designed for esthetic, acoustical and functional performance
- ▶ Unique, patent pending “Possible-To-Speak” indicator
- ▶ Easy and convenient to use
- ▶ Future-proof extensibility
- ▶ Digital acoustic feedback suppression

The CCS 900 Ultra Discussion System from Bosch brings order and convenience to small and middle-sized gatherings and conferences. This versatile and economical system is both simple to install and extremely straightforward to use. It has all the facilities required for achieving full control of meetings and discussions, without the need for an operator.

Technical specifications

Electrical

Mains voltage	100 to 240 VAC ± 10 %
Current consumption	maximum 0.9 A (100 VAC) to 0.3 A (240 VAC)
DC supply to contribution units	24 V ± 1 V (current limited)
Loudspeaker volume control	mute (50 dB att.) + 10 steps of 1.9 dB
Limiter threshold level to unit	10 dB above nominal level loudspeaker / headphone
Gain reduction due to number of open microphones (NOM)	÷ NOM ± 1 dB
Total harmonics	

Nominal input (85 dB SPL)	< 0.5
Max. input (110 dB SPL)	< 0.5

Mechanical

Dimensions including feet (H x W x D)	84 x 361 x 143 mm (3.4 x 14.2 x 5.6 in)
Height of feet	5.5 mm (0.22 in)
Mounting	tabletop (portable or fixed) 19-inch rack flush mounting
Weight	1.5 kg (3.3 lb)
Material (top)	polymer
Material (base)	painted metal
Color (top)	charcoal (PH10736)
Color (base)	black (PH80007)

Ordering information

CCS-CU Control Unit

CCS 900 control unit, supplies power for all delegate and chairman units in the system, as well as the unit microphones, provides connections for the audio inputs and outputs.

Order number **CCS-CU**

CCS-CUD Control Unit with DAFS

CCS 900 control unit with the DAFS (Digital Acoustic Feedback Suppression) facility, supplies the power for all delegate and chairman units in the system, as well as the unit microphones, provides connections for the audio inputs and outputs.

Order number **CCS-CUD**

CCS-CU-JP Control Unit (JP)

CCS 900 control unit, supplies the power for all delegate and chairman units in the system, as well as the unit microphones, provides connections for the audio inputs and outputs. Japanese version.

Order number **CCS-CU-JP**

CCS-CUD-JP Control Unit with DAFS (JP)

CCS 900 control unit with the DAFS (Digital Acoustic Feedback Suppression) facility, supplies power for all units in the system, as well as the unit microphones, provides connections for the audio inputs and outputs. Japanese version.

Order number **CCS-CUD-JP**

CCS-CU-US Control Unit (US)

CCS 900 control unit, supplies power for all delegate and chairman units in the system, as well as the unit microphones, provides connections for the audio inputs and outputs. US version.

Order number **CCS-CU-US**

CCS-CUD-US Control Unit with DAFS (US)

CCS 900 control unit with the DAFS (Digital Acoustic Feedback Suppression) facility, supplies power for all units in the system, as well as the unit microphones, provides connections for the audio inputs and outputs. US version.

Order number **CCS-CUD-US**

Represented by:

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
emea.securitysystems@bosch.com
emea.boschsecurity.com

Germany:

Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Germany
www.boschsecurity.com

North America:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.us

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia