

CCSD-CU-CN Control unit

www.boschsecurity.com



BOSCH

Invented for life



- ▶ Plug-and-play functionality for quick and easy connection of up to 80 Discussion Devices
- ▶ Intuitive web browser interface control for advanced configuration and control
- ▶ On-board support for automatic HD camera control

The Control Unit is the main component of the CCS 1000 D Digital Discussion System. It supplies DC power to all connected Discussion Devices (CCSD-DS/CCSD-DL) and monitors and controls the discussion system.

- Up to 80 Discussion Devices can be connected to a single Control Unit; the system can be expanded to a maximum of 245 Discussion Devices by using Extension Units (CCSD-EXU).
- Touch-button control allows for easy configuration and operation of the unit, while intuitive LED indicators give a clear indication of the system settings.
- Conveniently positioned connections at the rear of the unit enable peripheral equipment to be connected to the discussion system, such as audio equipment, Ethernet switches, video switches, Bosch HD Conference Domes, and a PC or laptop.
- An intuitive web browser interface control allows basic and advanced system settings to be easily viewed and changed, as required.

Functions

Plug-and-play functionality

The plug-and-play functionality of the Control Unit allows Discussion Devices and system cameras to be conveniently connected to and removed from the

system as required. A power down or restart of the system is not necessary, which ensures fast installation and reconfiguration times.

Web browser control

Basic and advanced system settings, including microphone management, can be easily viewed and configured using a web browser interface in combination with a tablet, laptop or PC.

- Changes made in the web browser interface are automatically updated in the Control Unit and vice-versa.
- An energy saving mode in the web browser interface allows the Control Unit and connected devices to automatically shut down if they are not used for two hours.
- The standby mode can be used during a meeting break. When this mode is selected, the Control Unit is set to standby and all Discussion Devices are switched off.
- The web browser interface also has an option to select a fixed IP address.

A RESTful API (Application Program Interface) can be used to:

- control the speaker's microphone.
- control the discussion modes and waiting lists.
- set the system to, and recover the system from, standby.
- retrieve and set the microphone sensitivity of an individual Discussion Device.

- facilitate web-casting and recorder solutions requiring microphone information, third-party Pan Tilt Zoom (PTZ) camera systems, and synoptic layouts for enabling and disabling microphones.

Microphone management

The maximum number of microphones that can be activated at the same time by pressing the microphone buttons on the Discussion Devices can be selected with the 'Number of Open Microphones' (NOM) button on the Control Unit.

- A maximum of four microphones can be selected on the Control Unit.
- This can be further extended to 25 microphones in the web browser interface.

Interruption microphone option

A Discussion Device can be configured as an interruption microphone that can always get the floor regardless of the number of open microphones. Typically an interruption microphone is positioned at a podium for use by guest speakers. The web browser interface allows a total of 25 Discussion Devices to be configured as interruption microphones or chairperson's devices.

Discussion modes

One of the following microphone modes can be selected by pressing the 'Microphone-mode' button on the front of the Control Unit:

- **Open mode** - Participants can speak by pressing their microphone buttons. When the maximum number of open microphones is reached, the next participant that presses their microphone button is added to a waiting list. The first participant in the 'waiting list' is allowed to speak when an activated microphone is disabled.
- **Override mode** - Participants can override each other by pressing their microphone buttons. When the maximum number of open microphones is reached, the next participant that presses their microphone button will deactivate the microphone that has been activated for the longest time (the chairperson's microphone is not included in the number of open microphones and, therefore, cannot be overridden by a participant).
- **Voice activation mode** - Participants can activate their microphones by speaking into them. A microphone can be temporarily muted by pressing and holding down the microphone button.
- **Push to talk (PTT) mode** - Participants can speak by pushing and holding in their microphone buttons. The microphone is deactivated when the microphone button is released. The maximum number of participants that can speak is determined by the number of open microphones.

Camera control

All Onvif Profile-S compliant cameras are automatically discovered.

The Camera Control offers:

- Control of Onvif Profile-S compatible cameras with username and password.
- Panasonic camera support via its IP protocol:

- AW-HE40, AW-HE50, AW-HE60, AW-HE120, AW-HE130, AW-UE70.
- Sony camera support via its IP protocol:
 - SRG-300SE and SRG 360SHE.
- Control of the TvOne CORIOmatrix and the Kramer MV-6 video switches.
- The enabling of HD-SDI video switching, so that HD SDI video signals can be automatically switched and displayed with low-latency on one or more hall displays.

Interface for connecting peripheral equipment

The Control Unit enables the following equipment to be connected to the Digital Discussion System:


- System cameras - for giving a clear visual overview of the proceedings. A maximum of six Bosch HD Conference Dome cameras can be connected to the system with native support (the camera presets can be configured in the web browser interface). The CCS 1000 D Digital Discussion System supports the tvONE CORIOmaster mini C3-510 and the Kramer MV-6 3G HD-SDI Multiviewer video switchers.
- External wired or wireless microphone - to allow a guest speaker or an audience to participate in a discussion.
- Sound reinforcement system - for transmitting the proceedings to an audience in the same room or an adjacent room.
- Audio equipment - for broadcasting music through the loudspeakers of the discussion system.
- External audio processor - for modifying the floor signal distributed to the participant loudspeakers and headphones (i.e. equalizing).
- Telephone coupler - to allow a remote participant to join a discussion via a telephone/video connection.
- External recorder - for recording and playing back discussions.

Controls and Indicators

- Mains power on/off button with red/green LED indicator. Red indicates that the system is off (no power available from the external power supply). Green indicates that the system is active (Control Unit and all connected devices powered up).
- Plus/minus buttons for setting the volume range of all connected Discussion Devices - used in combination with LED indicators for showing the selected volume.
- Microphone-mode button for selecting one of the microphone operating modes - used in combination with LED indicators for showing the selected mode.
- Open microphone button for selecting the number of microphones that can be activated at the same time - used in combination with LED indicators for showing the number of activated microphones.

Connections

Rear of unit:



CCSD-CU rear view

- 1 x 4-pole circular female 24 VDC power input connector.
 - 2 x 6-pole circular female connectors for loop-through connection of 40 Discussion Devices per trunk.
 - 1 x RJ45 Ethernet connector for communication with web browser interface application.
 - 1 x 3-pole XLR female microphone input connector with phantom supply.
 - 1 x RCA input for 'Floor' (i.e. external audio source, such as a CD or DVD player).
 - 1 x RCA output for a 'sound reinforcement system'.
 - 1 x RCA input/output for either:
 - 'Recorder' for connecting an external recorder.
 - 'Insertion' for connecting an external audio processor.
 - 'Telephone/mix minus' for allowing a remote participant to join a discussion via a telephone/video connection.
 - 'Participant loudspeaker' for distributing the participant loudspeaker signal to a sound reinforcement system.
- Only one piece of audio equipment can be connected to this RCA input/output at any one time. The RCA input/output has to be configured by selecting the required option in the web browser interface.

Certifications and approvals

EU	CE, WEEE ¹
US	UL, FCC
CA	CSA, ICES-003, EPS ¹
KR	KCC, KC ¹ , K-MEPS ¹
AU/NZ	RCM, MEPS ¹
RU/KZ/BY	EAC
JP	PSE ¹
CN	China RoHS, CCC ¹
TW	BSMI ¹
SA	SASO

Note: ¹ Only applicable for the power adaptor.

Region	Regulatory compliance/quality marks	
Europe	CE	DECL_EC_CCSD-CU

Parts included

Quantity	Component
1	CCSD-CU-CN Control unit
1	Mains power cord
1	24 VDC power supply
2	Sets of chairperson's buttons for a Discussion Device
1	Exchange tool for buttons
1	Set of feet for table top use
1	Set of 19" 1U mounting brackets
1	Safety instructions
1	Installation note
1	DVD with operation manual and supporting tools

Technical specifications

Electrical

Supply voltage Adaptor	100 to 240 VAC, 50/60 Hz
Current Consumption voltage Adaptor	1.9 A (100 VAC) to 1 A 240 (VAC)
DC voltage Control Unit	24 V, 6.0 A
Maximum number of Discussion Devices for Control Unit (without Extension Unit)	40 Discussion Devices per trunk 80 Discussion Device in total 24 V, Max 5.2 A (short-circuited protected)
Discussion Device loudspeakers volume control	15 steps of 1.5 dB (starting from -10.5 dB)
Limit threshold level to unit	12 dB above nominal level
Gain reduction due to number of open microphones (NOM)	1/SQRT (NOM)
Sample rate	44.1 kHz
Frequency response	30 Hz to 20 kHz
Ethernet speed	1 Gb/s

Total Harmonic Distortions (THD)

Nominal input (85 dB SPL)	< 0.5%
Max. input (110 dB SPL)	< 0.5%

Audio inputs

XLR nominal microphone input	-56 dBV
XLR maximum microphone input	-26 dBV
RCA nominal input	-24 dBV (+/- 6 dB)
RCA maximum input	+6 dBV

S/N	> 93 dBA
Frequency response	30 Hz to 20 kHz
THD	<0.1%

Audio outputs

RCA nominal output	-24 dBV (+6/- 24 dB)
RCA maximum output	+6 dBV
S/N	> 93 dBA
Frequency response	30 Hz to 20 kHz
THD	<0.1%

Mechanical

Dimensions including feet (H x W x D)	45 x 440 x 200 mm (1.8 x 17.3 x 7.9 in) 19" wide, 1 RU high
Height of feet	5.5 mm (0.2 in)
Mounting	Tabletop or 19 " rack
Material (top and base)	Painted metal
Color (top and base)	Traffic black (RAL 9017) matt-gloss
Rim front panel	Pearl light grey (RAL 9022) matt-gloss

Weight (CCSD-CU)	Approx. 3.2 kg (7.1 lb)
------------------	-------------------------

Environmental

Operating temperature	5 °C to +45 °C (+41 °F to +113 °F)
Storage and transport temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Relative humidity	5% to 98% non-condensing

Ordering information

CCSD-CU-CN Control unit

Control Unit for the CCS 1000 D Digital Discussion System, provides DC power for a maximum of 80 Discussion Devices, enables peripheral equipment to be connected to the system.

Order number **CCSD-CU-CN**

Services

EWE-CCSCU-IW 12mths wrty ext ccs control unit

12 months warranty extension

Order number **EWE-CCSCU-IW**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
emea.securitysystems@bosch.com
emea.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Germany
www.boschsecurity.com

North America:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.us

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia