

DCNM-FMICB Flush microphone button panel

DICENTIS



- ▶ Stylish and modern design
- ▶ Possible-to-speak indication available in the LED bar

The Microphone button panel is connected to the Flush base device (DCNM-FBD) via a control interface, and can be daisy-chained to other devices.

Functions

- The microphone has a LED bar that indicates:
 - Red: the microphone is active.
 - Green: the participant was added to the waiting list.
 - White: it is possible to speak.

Interconnections

- Control interface, through RJ12, to DCNM-FBD and other devices.
- Power and control interface to DCNM-FMCP.

Parts included

Quantity	Component
1	DCNM-FMICB Flush microphone button panel

Technical specifications

Mechanical

Mounting type	Click-to-fit in a metal panel with a thickness of 2 mm, or in combination with the DCN-FCOUP Flush coupling and the DCNM-FEC Flush end cap in any surrounding
Dimension (H x W x D) (mm)	56 mm x 50 mm x 46 mm
Dimension (H x W x D) (in)	2.20 in. x 2 in. x 1.80 in.
Weight (g)	43 g
Weight (lb)	0.09 lb
Color in RAL	RAL 9017 Traffic black

Environmental

According to IEC 60721: storage (1K3), transportation (2K2) and operational (3K4).

Operating temperature (°C)	5 °C – 45 °C
Operating temperature (°F)	41 °F – 113 °F
Transportation temperature (°C)	-30 °C – 70 °C

Represented by:

Europe, Middle East, Africa:
 Bosch Security Systems B.V.
 P.O. Box 80002
 5600 JB Eindhoven, The Netherlands
 Phone: + 31 40 2577 284
 emea.securitysystems@bosch.com
 www.boschsecurity.com

Germany:
 Bosch Sicherheitssysteme GmbH
 Robert-Bosch-Ring 5
 85630 Grasbrunn
 Germany
 www.boschsecurity.com

North America:
 Bosch Security Systems, LLC
 130 Perinton Parkway
 Fairport, New York, 14450, USA
 Phone: +1 800 289 0096
 Fax: +1 585 223 9180
 onlinehelp@us.bosch.com
 www.boschsecurity.us

Asia-Pacific:
 Robert Bosch (SEA) Pte Ltd, Security Systems
 11 Bishan Street 21
 Singapore 573943
 Phone: +65 6571 2808
 Fax: +65 6571 2699
 apr.securitysystems@bosch.com
 www.boschsecurity.asia

DCNM-FMICB Flush microphone button panel

DICENTIS

Transportation temperature (°F)	-22 °F – 158 °F
Storage temperature (°C)	-5 °C – 45 °C
Storage temperature (°F)	23 °F – 113 °F
Operating relative humidity, non-condensing (%)	5% – 90%

Ordering information

DCNM-FMICB Flush microphone button panel

Flush mounted microphone button panel.

Order number **DCNM-FMICB | F.01U.383.838**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
emea.securitysystems@bosch.com
emea.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Germany
www.boschsecurity.com

North America:
Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.us

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia