

DCNM-MICSLL Microphone screw lock long stem

DICENTIS



- ▶ Uni-directional microphone on adjustable stem
- ▶ Built-in pop and windshield
- ▶ Low susceptibility to mobile phones
- ▶ Screw lock robust connection

The innovative, stylish and ergonomically designed microphone with adjustable stem has a uni directional response for optimum performance, even in noisy conditions or acoustical challenging rooms. It has low susceptibility to interference from mobile phones.

Functions

Controls and indicators

- Red and green illuminator. Red indicates microphone active, green indicates request for speech accepted.

Interconnections

- Connector to plug and fasten the microphone.

Parts included

Quantity	Component
1	DCNM-MICSLL Microphone screw lock long stem

Technical specifications

Electrical

Power supply (VDC)	5 VDC
Power consumption (W)	0.10 W
Bandwidth (Hz)	125 Hz – 15 kHz
Dynamic range (dB)	100 dB
Nominal acoustic input level (dB SPL)	85 dB SPL

Maximum acoustic input level (dB SPL)	115 dB SPL
Equivalent noise (dB SPL)	15 dB SPL

Mechanical

Microphone stem length (mm)	480 mm
Microphone stem length (in)	19.90 in
Dimension (Ø x H) (mm) (connector)	41.3 mm x 15.9 mm
Dimension (Ø x H) (in) (connector)	1.63 in x 0.63 in
Weight (g)	108 g
Weight (lb)	0.28 lb
Color in RAL	RAL 9017 Traffic black

Environmental

According to IEC 60721: storage (1K3), transportation (2K2) and operational (3K4).

Operating temperature (°C)	5 °C – 45 °C
Operating temperature (°F)	41 °F – 113 °F
Transportation temperature (°C)	-30 °C – 70 °C
Transportation temperature (°F)	-22 °F – 158 °F
Storage temperature (°C)	-5 °C – 45 °C

Storage temperature (°F)	23 °F – 113 °F
Operating relative humidity, non-condensing (%)	5% – 90%

Ordering information

DCNM-MICSLL Microphone screw lock long stem

Screw locked microphone with long stem for the DICENTIS Conference system.

Order number **DCNM-MICSLL | F.01U.392.960**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Tel.: +49 (0)89 6290 0
Fax: +49 (0)89 6290 1020
de.securitysystems@bosch.com
www.boschsecurity.com

North America:
Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com