

# DCN-DV-CN Discussion device with voting

www.boschsecurity.com



**BOSCH**  
Invented for life



- ▶ Low susceptibility to mobile phone interference
- ▶ Compact, attractive and ergonomic design
- ▶ Five voting buttons
- ▶ Built-in loudspeaker and pluggable microphone
- ▶ Usable as delegate or chairman unit

This Delegate Unit with Voting enables participants to speak, register a request-to-speak, listen to the speaker and vote. A socket is provided to connect the pluggable microphones (DCN-MICS and DCN-MICL, to be ordered separately). The unit has five voting buttons for all types of voting. The yellow indicator rings around the voting buttons are used to prompt users to register their presence, to start voting and to confirm their votes. When the unit's attendance LED is yellow, it indicates the delegate is present.

## Functions

- Headphone output level reduction to prevent acoustic feedback (active when listening to the floor and when the microphone is on)
- The unit accommodates two headphone connections, so the speaker can be heard clearly even in situations with excessive background noise
- The built-in loudspeaker is muted when the microphone is on to prevent acoustic feedback

- The unit can be used a delegate unit, as a chairman unit (DCN-DBCM chairman buttons to be ordered separately) or as a delegate unit with auxiliary button. The auxiliary button is a versatile function, which can be used as an usher call for example
- To lock the loop-through cable, a cable clamp is available (DCN-DISCLM, to be ordered separately)
- The unit is available in a dark colored base

## Controls and Indicators

- Five voting buttons with indicator rings around the buttons
- Unit activity/delegate presence indicator
- Microphone button with a red, green or yellow illuminated LED. Red indicates microphone is active, green indicates request-to-speak accepted, and yellow indicates 'VIP'
- VIP indicator is lit when the delegate is part of the notebook (only available if PC Software is used)
- Headphone volume control buttons
- Recessed 'De-init' switch

## Interconnections

- Socket for pluggable microphone
- Two 3.5 mm (0.14 in) stereo jack type headphone sockets

- 2 m (78.7 in) cable terminated within a molded six-pole circular connector
- Six-pole circular connector for loop-through connections

### Certifications and approvals

Region	Regulatory compliance/quality marks	
Europe	CE	DECL EC DCN-DV

### Parts included

Quantity	Component
1	DCN-DV-CN Discussion device with voting

### Technical specifications

#### Electrical

Frequency response	30 Hz to 20 kHz
Headphone load impedance	> 32 Ohm < 1k Ohm
Output power	2 x 15 mW/32 Ohm

#### Mechanical

Mounting	Tabletop (portable or fixed mounting)
Dimensions (H x W x D)	<b>(without microphone)</b>

Tabletop	60 x 210 x 140 mm (2.36 x 8.27 x 5.51 in)
Weight	1.15 kg (2.54 lb)
Color top	Black (RAL 9017)
Color rear	Silver (RAL 9006)

### Ordering information

#### DCN-DV-CN Discussion device with voting

DCN Next Generation delegate unit with voting, pluggable microphone, dark. Chinese version. Microphone to be ordered separately.  
Order number **DCN-DV-CN**

#### Services

**EWE-DCNDIS-IW 12mths wrty ext DCN dicussion unit**  
12 months warranty extension  
Order number **EWE-DCNDIS-IW**

#### Represented by:

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
emea.securitysystems@bosch.com  
emea.boschsecurity.com

**Germany:**  
Bosch Sicherheitssysteme GmbH  
Robert-Bosch-Ring 5  
85630 Grasbrunn  
Germany  
www.boschsecurity.com

**North America:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
onlinehelp@us.bosch.com  
www.boschsecurity.us

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia