



DCN-FVCRD Flush Voting ID Card Panel



- ▶ **Stylish and modern design (IF award)**
- ▶ **Identification with ID card**
- ▶ **External Present contact**
- ▶ **LED vote confirmation indicators**
- ▶ **LED unit active indicator**

The Flush Voting ID Card Panel has the same functionality as the Flush Voting Panel (DCN-FV) with the addition of an ID card reader.

The ID card reader enables identification of delegates to the DCN Next Generation system, as well as providing a convenient facility that ensures only authorized delegates can participate in voting sessions or general conference proceedings such as microphone use. The unit is connected to the Dual Delegate Interface DCN-DDI.

Functions

Controls and Indicators

Front

- Five voting buttons with yellow confirmation indicators to prompt the user to indicate presence, to vote and to confirm registration of what is voted. The buttons and indicators work as follows:
 - Yes (+), no (-) and abstain (x) (used for attendance registration, parliamentary voting and for/against)
 - Numerals 1 to 5 (used for multiple choice, opinion polls and rating)
 - Rating scale: -, -, 0, +, ++ (used for audience response)
- One blue LED unit active indicator to show that the system is in normal operation. The yellow LED indicates the validity of the ID card

Interconnections

- 2 RJ11 connectors, one for connection to DCN-DDI Dual Delegate Interface and one for loop through
- Connector for an external present contact (AMP173977-3 socket)

Technical Specifications

Mechanical

Mounting	Click-to-fit in a metal panel with a thickness of 2 mm, or in combination with DCN-FCOUP couplings and DCN-FEC end caps in any surrounding
Dimensions (H x W x D)	40 x 100 x 82 mm (1.57 x 3.94 x 3.23 in)
Weight	104 g (0.23 lb)
Color	
DCN-FVCRD	Silver (RAL 9022)

Ordering Information

DCN-FVCRD Flush Voting ID Card Panel flush mounted, silver	DCN-FVCRD
--	------------------

Americas:

Bosch Communications Systems
12000 Portland Avenue South
Burnsville, Minnesota, 55337, USA
Phone: +1-800-392-3497
Fax: +1-800-955-6831
audiosupport@us.bosch.com
www.boschcommunications.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Bosch Security Systems Pte Ltd
38C Jalan Pemimpin
Singapore 577180
Phone: +65 6319 3450
Fax: +65 6319 3499
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by