

DIVAR IP all-in-one 7000 2U (gen 3)



The DIVAR IP all-in-one 7000 family is an affordable, simple and reliable all-in-one recording, viewing and management solution for network surveillance systems of up to 256 channels (with 8 channels prelicensed).

DIVAR IP all-in-one 7000 2U is a 2U rack mount unit that combines advanced Bosch Video Management System capabilities and state-of-the-art recording management into a single cost-effective, convenient to install and operate recording device for IT-minded customers.

System overview

The DIVAR IP all-in-one 7000 family utilizes an energy efficient, embedded design which reduces possible points of failure and boasts Bosch quality through-and-through. Utilizing "enterprise-rated" hard drives in a fault tolerant RAID-5 configuration, dual port Gigabit Ethernet network interface, 16 GB system memory and an Intel Xeon Hexa Core Processor, the device delivers high-end performance at a very affordable price.

Easy to install and operate, the system features wizard-based set-up and centralized configuration.

Operation modes

DIVAR IP all-in-one 7000 systems can operate in three different modes:

 Full video recording and management system, utilizing the BVMS and Video Recording Manager core components and services.













- ➤ RAID-5 protected (standard configuration), allin-one video management solution for up to 256 channels
- ► Out-of-the-box IP video management solution with up to 96 TB storage capacity
- ► Instantly find what you are looking for
- ► BVMS-based advanced user and alarm management
- ► DIVAR IP System Manager for operation mode selection, software setup and upgrades

This mode provides an advanced IP video security solution that delivers seamless management of digital video, audio and data across an IP network. It seamlessly combines IP cameras and encoders, provides system-wide event and alarm management, system health monitoring, user and priority management. This mode provides the best video management system to go with Bosch video surveillance devices, leveraging the unique capabilities of Bosch cameras and recording solutions. It includes Video Streaming Gateway components to integrate third-party cameras.

- Advanced video recording solution for a BVMS system, utilizing the Video Recording Manager core components and services, leveraging the unique capabilities of Bosch cameras and recording solutions. Up to two Video Recording Manager servers can be added to a BVMS system running on a DIVAR IP all-in-one device.
- iSCSI storage expansion for a BVMS system, which runs on a different hardware. Up to four of these iSCSI storage expansions can be added to a BVMS system running on a DIVAR IP all-in-one 7000 device.

Functions

The DIVAR IP all-in-one 7000 2U units feature highly energy-efficient hot-swap redundant power supplies, as well as front-swappable SATA-3 hard drives

providing up to 96 TB of gross storage capacity. The DIVAR IP all-in-one 7000 2U units utilize Microsoft Windows Server IoT 2019 for Storage Standard.

Instant real time access to video

View high quality HD and even UHD video despite low or limited bandwidth connections.

Dynamic Transcoding technology ensures you can view your video immediately - anytime, anywhere. The built-in transcoder supports up to 2 x UHD resolution video streams in parallel.

Management and health monitoring

DIVAR IP System Manager provides a central user interface for operation mode selection and for software setup and upgrade, which reduces installation and training requirements and keeps ongoing system management costs low.

When DIVAR IP all-in-one is connected to the Bosch Remote Portal, Remote System Management service allows to leverage the power of the Internet of Things (IoT) to provide an easy-to-use set of tools and capabilities for secure, transparent and cost-effective asset management throughout the life cycle of a device or system. This service enables users to perform inventory and update management, as well as health monitoring tasks for an entire system from one centralized Remote Portal platform.

The DIVAR IP all-in-one 7000 devices provide SNMP monitoring support for the system's hardware and for the video management applications to ensure maximum uptime.

BMC (IPMI) controller operating via dedicated Ethernet LAN port allows the user to access, monitor, diagnose, and manage DIVAR IP all-in-one 7000 as a remote server.

Remote viewing

For remote viewing of a single DIVAR IP all-inone 7000 system, BVMS Operator Client is included. For multiple systems, add them to BVMS Enterprise Management Server.

Alternatively, use Video Security Client for viewing video from a separate workstation or mobile device.

Regulatory information			
Certifications/ Directives	CB, UL, CE, UKCA, FCC, VCCI, RCM, KC, BSMI, SABS, NRCS LOA, RoHS, WEEE, BIS, NDAA, TAA		
Region	Regulatory	compliance/quality marks	
Morocco	CMIM		
Great Britain	UKCA		
Global	IEC 62443	Industrial Cyber Security Capability	
Europe	CE		

Installation/configuration notes



Notice

Environmental conditions

Install the system in a clean, dust-free, dry and weather-protected area that is well ventilated. Avoid areas where heat, electrical noise and electromagnetic fields are generated. The standard warranty coming with the system will be void if evidence is seen that the system was exposed to conditions contradicting the environmental conditions mentioned here.

Configuration of new hard drives

DIVAR IP all-in-one units that come pre-equipped with hard drives from factory are ready to record out-of-the-box. Hard drives that have been added to an empty unit need to be configured before using them for video recording.

The RAID configuration of new hard drives must be set up manually via the pre-installed RAID management utility. Only after this manual RAID configuration the DIVAR IP all-in-one 7000 system provides full functionality.

RAID configuration

DIVAR IP all-in-one 7000 2U units come pre-configured in a RAID-5 standard configuration with iSCSI LUNs (fully populated system only) and provide the following specifications:

RAID-5 configuration

Gross Ca- pacity	Net Capa- city	Bandwidth*	IP Cameras
w/o HDD	n/a	550 Mbit/s	256 max.
8 x 4 TB	26068 GB	550 Mbit/s	256 max.
8 x 8 TB	52136 GB	550 Mbit/s	256 max.
8 x 12 TB	78204 GB	550 Mbit/s	256 max.

^{*}Performance only warranted with hard drive models tested and qualified by Bosch.

These values refer to the BVMS recording engine; Net capacity for a RAID-5 configuration without hot spare; 256 connected IP cameras indicate the number of concurrent recordable cameras plus 8 sessions for replay.

Optional supported RAID configurations are RAID-5 with 1 x hot spare or RAID-6 without hot spare. The optional RAID configurations will not come preconfigured but must be set up manually via the preinstalled RAID configuration utility.

RAID-5 plus hot spare configuration

Gross Ca- pacity	Net Capa- city	Bandwidth*	IP Cameras
w/o HDD	n/a	550 Mbit/s	256 max.

Gross Ca- pacity	Net Capa- city	Bandwidth*	IP Cameras
8 x 4 TB	22344 GB	550 Mbit/s	256 max.
8 x 8 TB	44688 GB	550 Mbit/s	256 max.
8 x 12 TB	67032 GB	550 Mbit/s	256 max.

^{*}Performance only warranted with hard drive models tested and qualified by Bosch.

RAID-6 configuration

Gross Ca- pacity	Net Capa- city	Bandwidth*	IP Cameras
w/o HDD	n/a	550 Mbit/s	256 max.
8 x 4 TB	22344 GB	550 Mbit/s	256 max.
8 x 8 TB	44688 GB	550 Mbit/s	256 max.
8 x 12 TB	67032 GB	550 Mbit/s	256 max.

^{*}Performance only warranted with hard drive models tested and qualified by Bosch.

License limitations

For the BVMS licenses applied on DIVAR IP all-inone 7000 units, note pre-licensed quantities, quantities that come with the base license, and the upper limit of each:

License type	Pre-licensed	Base license MBV-BPLU- DIP	Upper limit
IP channel	8	32	256
Workstation client	2	5	20
DVR	1	1	10
CCTV Keyboard	2	5	10
Mobile Video Service	1*	1*	4*
Subsystems	0	0	20
Intrusion Panel	1	1	10
Failover VRM chan- nel	0	8	256
Dual recording channel	0	8	256
Unmanaged Site	0	1	20
LPR channel	0	0	10

License type	Pre-licensed	Base license MBV-BPLU- DIP	Upper limit
Online map functionality (BVMS 11.0 and later)	0	0	1
Map-based track- ing assistant (BVMS 11.0 and later)	0	0	1
Privacy over- lay(BVMS 12.0.0 and later)	0	0	1

^{*}Mobile Video Service needs to run on separate hardware.

For further details, see the BVMS documentation.

(i) Notice

Uninterruptable Power Supply (UPS). We strongly recommend using an "Online UPS" with an always active battery. The UPS must support Microsoft Windows Storage Server 2019 and must be sufficient to allow time to bring an auxiliary power source on line, or to properly shut down the DIVAR IP disk array(s).

(i) Notice

Bosch is not liable for any data loss, damages, or system failures of units equipped with hard drives that are not supplied by Bosch. Bosch cannot provide support if non-Bosch-supplied hard drives are considered to be the cause of the problem. To troubleshoot potential hardware issues, Bosch will require Bosch-supplied hard drives to be installed.

(i)

Notice

Hardware warranty

DIVAR IP all-in-one devices come with a 3-year service level agreement that covers on-site service on the next business day. This service level can only be provided if the respective system has been registered immediately after receipt and installation. Otherwise, service will be provided based on best effort basis. Information about registration details is available in every shipment (registration form) or from the Bosch online product catalog. Next business day services cannot be provided in every country everywhere. For limitations and exceptions see the registration details in the registration form. If you order the warranty extension together with the device, refer to the "PoS" item in the price list. You can also order the warranty extension once the device is out of warranty. For this option, refer to the Bosch technical support.

i Notice

Software maintenance

Maintenance of software components is not included in this product.

A separate maintenance agreement needs to be purchased, in order to receive updates and technical support for the installed software.For more details on the Bosch Software Assurance, refer to: https://www.boschsecurity.com/xc/en/solutions/management-software/boschsoftware-assurance/

Technical specifications

Electrical

Type of power supply	VAC
Operating voltage (VAC)	100 - 240 VAC
Maximum output power (W)	800 W
Power frequency	50 Hz; 60 Hz
Power supply efficiency rating	80 PLUS Titanium

120 VAC input (under highest capacity)

Rated input current (A)	2.1 A
Actual output wattage from power supply (W)	228.8 W
Efficiency of power supply (%)	94%
Power consumption* (W)	243.4 W max.
Maximum heat loss (BTU/h)	830.7 BTU/h

Power factor	0.98
System AC input VA requirement	248.3 VA

^{*}System power consumption may vary based on workload and environment.

240 VAC input (under highest capacity)

Rated input current (A)	1.0 A
Actual output wattage from power supply (W)	228.8 W
Efficiency of power supply (%)	96%
Power consumption* (W)	238.3 W max.
Maximum heat loss (BTU/h)	813.4 BTU/h
Power factor	0.96
System AC input VA requirement	248.2 VA

^{*}System power consumption may vary based on workload and environment.

Mechanical

Mechanical	
Dimension (H x W x D mm)	89 x 437 x 648 mm
Dimension (H x W x D in)	3.5 x 17.2 x 25.5 in
Mounting type	rack-mounted
Rack unit (U)	2 U
	DIP-7380-00N Management appliance, 2U w/o HD 3rd gen
Weight (kg)	16.50 kg
Weight (lb)	36.39 lb
	DIP-7384-8HD Management appliance, 2U 8X4TB 3rd gen
Weight (kg)	21.90 kg
Weight (lb)	48.39 lb
	DIP-7388-8HD Management appliance, 2U 8X8TB 3rd gen
Weight (kg)	22.70 kg
Weight (lb)	50.15 lb
	DIP-738C-8HD Management appliance, 2U 8X12TB 3rd gen
Weight (kg)	22.10 kg

	DIP-738C-8HD Management appliance, 2U 8X12TB 3rd gen
Weight (lb)	48.79 lb
Environmental	
Operating temperature (°C)	10 - 35 °C
Operating temperature (°F)	50 - 95 °F
Storage temperature (°C)	-40 - 70 °C
Storage temperature (°F)	40 - 158 °F
Operating relative humidity, non- condensing (%)	8 - 90 %
Storage relative humidity (%)	5 - 95 %
Operation	
Processor	Intel® Xeon® E-2226GE
Processor base frequency	3.40 GHz
Cache	12 MB Intel® Smart Cache
Installed memory	16GB DDR4-2666 2Rx8 ECC UDIMM
Memory protection	ECC unbuffered
Operating system	Microsoft Windows Server IoT 2019 for Storage Standard
Processor graphics	Intel HD onboard graphics (three digital outputs: 1 DVI-I port, 2 Display-Port ports), VGA disabled
SAS RAID Card	12Gb/s Eight-Port
Software compatibility	Web browser; Bosch Configuration Manager; Bosch Video Management System; Video Recording Manager; Video Security App
Storage	
Internal storage	HDD
HDD connectivity	SATA3
HDD dimension	3.5 inch
Maximum internal hard drives	8
HDD rotation speed (rpm)	7200 rpm
Optical drive type	DVD double layer

OS storage	2x240 GB SSD RAID-1 configuration
Connectivity	
Number of USB ports	6 Front: 2 USB 2.0 ports Rear: 3 USB 3.1 ports and 1 USB-C port
Number of Ethernet ports	2 RJ45 Gigabit Ethernet LAN ports (teamed)
Network port	1 IPMI BMC port
Number of video outputs	 3 2 x DP 1.2, 4K@60Hz 1x DVI-I, 1920x1080 @60Hz
Multi-display support	Maximum of 3 displays of up to 4K@30Hz resolution per display (DisplayPort) and 1920x1080@60Hz (DVI-I)
Data security	

Ordering information

Crypto coprocessor (TPM)

DIP-7380-00N Management appliance, 2U w/o HD 3rd gen

Discrete TPM 2.0

All-in-one recording, viewing and management solution for network surveillance systems.

Without HDD.

NDAA compliant

Order number DIP-7380-00N | F.01U.385.539

DIP-7384-8HD Management appliance, 2U 8X4TB 3rd gen

All-in-one recording, viewing and management solution for network surveillance systems.

With 8 x 4 TB storage capacity.

NDAA compliant

Order number DIP-7384-8HD | F.01U.385.540

DIP-7388-8HD Management appliance, 2U 8X8TB 3rd gen

All-in-one recording, viewing and management solution for network surveillance systems.

With 8 x 8 TB storage capacity.

NDAA compliant

Order number DIP-7388-8HD | F.01U.385.541

DIP-738C-8HD Management appliance, 2U 8X12TB 3rd

All-in-one recording, viewing and management solution for network surveillance systems.

With 8 x 12 TB storage capacity.

NDAA compliant

Order number **DIP-738C-8HD | F.01U.385.542**

Accessories

DIP-AIO4-HDD 4TB HDD DIVAR IP all-in-one

Hard disk storage expansion for DIVAR IP all-in-one appliances with a capacity of 4 TB.

Order number DIP-AIO4-HDD | F.01U.362.421

DIP-AIO8-HDD 8TB HDD DIVAR IP all-in-one

Hard disk storage expansion for DIVAR IP all-in-one appliances with a capacity of 8 TB.

Order number **DIP-AIO8-HDD | F.01U.362.420**

DIP-AIO12-HDD 12TB HDD DIVAR IP all-in-one

Hard disk storage expansion for DIVAR IP all-in-one appliances with a capacity of 12 TB.

Order number **DIP-AIO12-HDD | F.01U.362.419**

DIP-AIO18-HDD 18TB HDD DIVAR IP all-in-one

Hard disk storage expansion for DIVAR IP all-in-one appliances with a capacity of 18 TB.

Order number **DIP-AIO18-HDD | F.01U.404.044**

KBD-UXF Keyboard, USB CCTV-oriented

USB CCTV-oriented keyboard for use with BVMS, BIS -Video Engine, or DIVAR IP systems.

Order number KBD-UXF | F.01U.279.328

Software Options

MBV-BPLU-DIP License Plus base for DIP AIO 6000-7000

BVMS license for DIVAR IP all-in-one 6000 and DIVAR IP all-in-one 7000.

Base license for 32 channels (cameras/decoders). Order number MBV-BPLU-DIP | F.01U.374.503

MBV-XCHANPLU License Camera/decoder expansion

Expansion license for 1 encoder/decoder channel. Order the exact number required.

Order number MBV-XCHANPLU | F.01U.393.681

MBV-XWSTPLU License Workstation expansion

Expansion license for 1 workstation (each extra workstation requires 1 license).

Order number MBV-XWSTPLU | F.01U.393.682

MBV-XDVRPLU License DVR expansion

Expansion license for 1 DVR. Order the exact number required.

Order number MBV-XDVRPLU | F.01U.393.683

MBV-XKBDPLU License Keyboard expansion

Expansion license for 1 CCTV keyboard. Order the exact number required.

Order number MBV-XKBDPLU | F.01U.393.684

MBV-XMVSPLU License Mobile video service expansion

Expansion license for 1 Mobile Video Service. Order number MBV-XMVSPLU | F.01U.393.685

MBV-XSUBPLU License Subsystem expansion

Expansion license for 1 subsystem. Order the exact number required.

Order number MBV-XSUBPLU | F.01U.393.692

MBV-XINTPLU License Intrusion panel expansion

Expansion license to integrate intrusion panels. Order number MBV-XINTPLU | F.01U.393.689

MBV-XFOVPLU License VRM Failover channel expansion

Expansion license for 1 encoder channel used with a Failover VRM.

Order number MBV-XFOVPLU | F.01U.393.686

MBV-XDURPLU License Camera dual recording

Expansion license for 1 encoder channel used for dual recording.

Order number MBV-XDURPLU | F.01U.393.687

MBV-XSITEPLU License Unmanaged site expansion

Expansion license for 1 site. Order the exact number required.

Order number MBV-XSITEPLU | F.01U.393.688

MBV-XLPRPLU License LPR camera expansion

Expansion license for 1 (Tattile) LPR camera. Order the exact number required.

Order number MBV-XLPRPLU | F.01U.393.691

MBV-FMAPPLU License online map functionality

Expansion license for online map functionality. Order number MBV-FMAPPLU | F.01U.395.079

MBV-FOBJPLU License Map-based tracking assistant

Expansion license for Map-based tracking assistant. Order number MBV-FOBJPLU | F.01U.393.652

MBV-FPRIPLU License Privacy overlay

Expansion license for Privacy overlay.

Order number MBV-FPRIPLU | F.01U.414.239

CBS-RM-DIP7 Remote System Management DIP 7000

License to enable Remote System Management services for one DIVAR IP all-in-one 7000 (DIP-72xx, DIP-73xx) device for a 1 year period

Order number CBS-RM-DIP7 | F.01U.410.887

MBV-MPLU-DIP SMA license for MBV-BPLU-DIP, 1 year

One year of maintenance cover for the BVMS license for DIVAR IP all-in-one 6000 and DIVAR IP all-in-one 7000. Order number MBV-MPLU-DIP | F.01U.389.513

MBV-MCHANPLU SMA license for MBV-XCHANPLU, 1 year

1 year of maintenance cover for the Plus Edition camera/ decoder expansion license.

Order number MBV-MCHANPLU | F.01U.330.514

MBV-MWSTPLU SMA license for MBV-XWSTPLU, 1 year

1 year of maintenance cover for the Plus Edition workstation expansion license.

Order number MBV-MWSTPLU | F.01U.330.515

MBV-MDVRPLU SMA license for MBV-XDVRPLU, 1 year 1 year of maintenance cover for the Plus Edition DVR

expansion license.

Order number MBV-MDVRPLU | F.01U.330.517

MBV-MKBDPLU SMA license for MBV-XKBDPLU, 1 year

1 year of maintenance cover for the Plus Edition keyboard expansion license.

Order number MBV-MKBDPLU | F.01U.330.518

MBV-MMVSPLU SMA license for MBV-XMVSPLU, 1 year

1 year of maintenance cover for the Plus Edition Mobile Video Service expansion license.

Order number MBV-MMVSPLU | F.01U.330.519

MBV-MSUBPLU SMA license for MBV-XSUBPLU, 1 year

One year of maintenance cover for an Enterprise Subsystem expansion license.

Order number MBV-MSUBPLU | F.01U.389.490

MBV-MINTPLU SMA license for MBV-XINTPLU, 1 year

One year of maintenance cover for the BVMS Plus Intrusion panel expansion license.

Order number MBV-MINTPLU | F.01U.330.522

MBV-MFOVPLU SMA license for MBV-XFOVPLU, 1 year

 ${\bf 1}$ year of maintenance cover for the Plus Edition Failover VRM expansion license.

Order number MBV-MFOVPLU | F.01U.330.520

MBV-MDURPLU SMA license for MBV-XDURPLU, 1 year

1 year of maintenance cover for the Plus Edition Dual Recording VRM expansion license.

Order number MBV-MDURPLU | F.01U.330.521

MBV-MSITEPLU SMA license for MBV-XSITEPLU, 1 year

One year of maintenance cover for the site expansion license.

Order number MBV-MSITEPLU | F.01U.381.964

MBV-MLPRPLU SMA license for MBV-XLPRPLU, 1 year

1 year of maintenance cover for the (Tattile) LPR camera expansion license.

Order number MBV-MLPRPLU | F.01U.389.491

MBV-MMAPPLU SMA license for MBV-FMAPPLU, 1 year

One year of maintenance cover for an online map functionality license.

Order number MBV-MMAPPLU | F.01U.395.082

MBV-MOBJPLU SMA license for MBV-FOBJPLU, 1 year

One year of maintenance cover for the Map-based tracking assistant license.

Order number MBV-MOBJPLU | F.01U.393.694

MBV-MPRIPLU SMA license for MBV-FPRIPLU, 1 year

One year of maintenance cover for a Privacy overlay license.

Order number MBV-MPRIPLU | F.01U.414.322

Services

EWE-7380S0N-IW DIP-7380-00N SRV Ext. 12 Mths IW

12 months warranty extension

Order number EWE-7380S0N-IW | F.01U.395.186

EWE-7384S8H-IW DIP-7384-8HD SRV Ext. 12 Mths IW

12 months warranty extension

Order number EWE-7384S8H-IW | F.01U.395.187

EWE-7388S8H-IW DIP-7388-8HD SRV Ext. 12 Mths IW

12 months warranty extension

Order number EWE-7388S8H-IW | F.01U.395.188

EWE-738CS8H-IW DIP-738C-8HD SRV Ext. 12 Mths IW

12 months warranty extension

Order number EWE-738CS8H-IW | F.01U.395.189

Represented by:

Europe, Middle East, Africa:

Bosch Security Systems B.V. P.O. Box 80002 5600 JB Eindhoven, The Netherlands Phone: + 31 40 2577 284 www.boschsecurity.com/xc/en/contact/ www.boschsecurity.com

Germany:

Bosch Sicherheitssysteme GmbH Robert-Bosch-Ring 5 85630 Grasbrunn Tel.: +49 (0)89 6290 0 Fax:+49 (0)89 6290 1020 de.securitysystems@bosch.com www.boschsecurity.com

North America:

Bosch Security Systems, LLC 130 Perinton Parkway Fairport, New York, 14450, USA Phone: +1 800 289 0096 Fax: +1 585 223 9180 onlinehelp@us.bosch.com www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems 11 Bishan Street 21 Singapore 573943 Phone: +65 6571 2808 Fax: +65 6571 2699 www.boschsecurity.com/xc/en/contact/ www.boschsecurity.com