FLM-320-EOL2W End-of-line module, 2-wire

www.boschsecurity.com







► For installations with Extended Line Supervision (ELS)

The EOL module terminates conventional lines for creeping open monitoring (ELS, formerly EN 54-13 requirement).

It detects primary line faults and reports them to the fire panel.

Certifications and approvals

Region	Regulatory compliance/quality marks	
Germany	VdS	G 210007 FLM-320-EOL2W
Europe	CE	FLM-320-EOL2W
	CPD	0786-CPD-20926 FLM-320-EOL2W

Parts included

Quantity	Component
1	FLM-320-EOL2W Conventional EOL Module

Technical specifications

Electrical

Operating voltage	9 V DC to 30 V DC
Current consumption	< 2.0 mA

Mechanics

Housing material	Thermelt 861
Housing color	black
Dimensions (H x W x D)	25 x 17 x 8 mm
Weight	7 g

Environmental conditions

Permissible operating temperature	-25°C to 70°C
Permissible storage temperature	-25°C to 85°C
Permissible relative humidity	<96%, non condensing
Protection class as per IEC 60529	IP 30

Ordering information

FLM-320-EOL2W End-of-line module, 2-wire

for termination of 2-wire conventional line with Extended Line Supervision (ELS)
Order number FLM-320-EOL2W