



# Lockable code keypad



The lockable code keypad, used in conjunction with the reader, allows arming and disarming of the intrusion alarm system only after the correct combination of numbers has been entered at the keypad.

## Functions

If someone is forced to disarm the intrusion alarm system, a silent alarm (hold-up alarm) can be set off remotely via the code keypad. The code keypad is mounted outside the secured area.

## Certifications and Approvals

Region	Certification	
Germany	VdS	G 193010, C Abschließbare Codetastatur
Europe	CE	Codetastatur

## Technical Specifications

### Lockable code keypad

#### Environmental conditions

- Environmental class 3
- Protection category IP 32
- Operating temperature -25 °C to +60 °C
- Storage temperature -30 °C to +60 °C

#### Housing

- Color RAL 9002
- Dimensions (H x W x D) 164 x 73 x 36 mm

#### Flush-mounted mounting kit

#### Dimensions (H x W x D)

- Flush-mounted use 180 x 92 x 35 mm
- Frame 194 x 104 x 23 mm

Color RAL 9002

## Ordering Information

### Lockable code keypad

**2799380623**

Can be used in conjunction with the reader

**Americas:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: +31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**  
Bosch Security Systems Pte Ltd  
38C Jalan Pemimpin  
Singapore 577180  
Phone: +65 6319 3450  
Fax: +65 6319 3499  
apr.securitysystems@bosch.com  
www.boschsecurity.com

**Represented by**