DCN-DISV Discussion Unit with Voting

www.boschsecurity.com





- Low susceptibility to mobile phone interference
- Compact, attractive and ergonomic design
- Pluggable microphone
- ► Five voting buttons
- Built-in loudspeaker

This Discussion Unit with Voting enables participants to speak, register a request-to-speak, listen to the speaker and vote. A socket is provided to connect the pluggable microphones (DCN-MICS and DCN-MICL, to be ordered separately). The unit has five voting buttons for all types of voting. The yellow indicator rings around the voting buttons are used to prompt users to register their presence, to start voting and to confirm their votes. When the unit's attendance LED is yellow, it indicates the delegate is present.

Functions

- Headphone output level reduction to prevent acoustic feedback (active when listening to the floor and when the microphone is on)
- The unit accommodates two headphone connections, so the speaker can be heard clearly even in situations with excessive background noise
- The built-in loudspeaker is muted when the microphone is on to prevent acoustic feedback
- A variety of rims are available, so the unit can be matched to the interior. (DCN-DISR, to be ordered separately).

- The unit can be used a delegate unit, as a chairman unit (DCN-DISBCM chairman buttons to be ordered separately) or as a delegate unit with auxiliary button. The auxiliary button is a versatile function, which can be used as an usher call for example
- To lock the loop-through cable, a cable clamp is available (DCN-DISCLM, to be ordered separately)
- The unit is available in light and dark colored bases

Controls and Indicators

- Five voting buttons with indicator rings around the buttons
- Unit activity/delegate presence indicator
- Microphone button with a red, green or yellow illuminated ring. Red indicates microphone is active, green indicates request-to-speak accepted, and yellow indicates 'VIP'
- VIP indicator is lit when the delegate is part of the notebook (only available if PC Software is used)
- Headphone volume control buttons
- Recessed 'De-init' switch

Interconnections

- Socket for pluggable microphone
- Two 3.5 mm (0.14 in) stereo jack type headphone sockets
- 2 m (78.7 in) cable terminated within a molded sixpole circular connector

• Six-pole circular connector for loop-through connections

Certifications and approvals

CF

Region Europe

Certification

Technical specifications

Electrical

Frequency response	30 Hz to 20 kHz
Headphone load impedance	> 32 ohm < 1k ohm
Output power	2 x 15 mW/32 ohm

Mechanical

Mounting	Tabletop (portable or fixed mounting) and flush mounting
Dimensions (H x W x D)	(without microphone)
Tabletop	61 x 190 x 116 mm (2.4 x 7.5 x 4.6 in)
Flush mounted	6 x 190 x 120 mm (0.2 x 7.5 x 4.7 in)
Weight	800 g (1.76 lb)
Color top	Silver (RAL 9022)
Color base	
DCN-DISV-L	Light Grey (RAL 000 7500)
DCN-DISV-D	Charcoal (PH 10736)

Ordering information

DCN-DISV-L Discussion Voting Light

pluggable microphone, light base, microphone and rims to be ordered separately Order number DCN-DISV-L

DCN-DISV-D Discussion Voting Dark

pluggable microphone, dark base, microphone and rims to be ordered separately Order number DCN-DISV-D

DCN-MICS Pluggable Short Microphone length 310 mm (12.2 inch), silver Order number DCN-MICS

DCN-MICL Pluggable Long Microphone

length 480 mm (18.9 inch), silver Order number **DCN-MICL**

DCN-DISRH-SR Rim High Gloss Silver (10 pcs) silver, high gloss, 10 pieces

Order number DCN-DISRH-SR

DCN-DISR-SR Rim Silver (10 pcs)

silver, 10 pieces Order number DCN-DISR-SR DCN-DISR-D Rim Dark (10 pcs) dark, 10 pieces Order number DCN-DISR-D

DCN-DISRMH Rim Metal High Gloss (10 pcs) metal, high gloss, 10 pieces Order number DCN-DISRMH

DCN-DISRMS Rim Metal Semi Gloss (10 pcs) metal, semi gloss, 10 pieces Order number DCN-DISRMS

DCN-DISBCM Buttons Chairman (10 sets) 10 sets Order number DCN-DISBCM

DCN-DISBDD Buttons Dual Use (10 sets) 10 sets Order number DCN-DISBDD

DCN-DISCLM Cable Clamp (25 pcs) 25 pieces Order number DCN-DISCLM

Represented by:

Americas:

Americas: Bosch Security Systems, Inc. 12000 Portland Avenue South Burnsville MN 55337, USA Phone: +1-800-392-3497 Fax: +1-800-955-6831 audiosupport@us.bosch.com www.boschsecurity.com

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002

P.O. Box 80002 5617 BA Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com

@ Bosch Security Systems 2013 | Data subject to change without notice 1781935115 | en, V5, 03. Jun 2013

Asia-Pacific:

Asia-Pacific: Robert Bosch (SEA) Pte Ltd, Security Systems 11 Bishan Street 21 Singapore 573943 Phone: +65 6571 2808 Fax: +65 6571 2609 apr.securitysystems@bosch.com www.boschsecurity.asia

China:

China: Bosch (Shanghai) Security Systems Ltd. 201 Building, No. 333 Fuquan Road North IBP Changning District, Shanghai 200335 China Phone +86 21 22181111 Fax: +86 21 22182398 www.bacsbecurity.com.cn www.boschsecurity.com.cn

America Latina:

America Latina: Robert Bosch Ltda Security Systems Division Via Anhanguera, Km 98 CEP 13065-900 Campinas, Sao Paulo, Brazil Phone: +55 19 2103 2860 Fax: +55 19 2103 2862 al.securitysystems@bosch.com www.boschsecurity.com