



# LBB 4410/00 Network Splitter



- ▶ Two current-limited network tap-offs
- ▶ Supports redundant network connection on main loop
- ▶ Can feed power from an external supply to the network
- ▶ Power 'ON' indication
- ▶ Fault indication

The network splitter is used in a network to provide two branches from the main cable run. It can use an external DC power supply, or it can use the power supply from the network controller. The unit automatically switches to the local power supply unit when it is connected to it, reducing the power drain on the main network. The network splitter can also function as a repeater, effectively extending the length of the main network another 50 meters.

## Functions

The splitter inserts Praesideo units connected to a tap-off into the main network, however without the redundancy of the main loop. The maximum current supplied for each of the two tap-offs is separately selectable. External power from the local supply is used only for the tap-offs, and is not fed into the main system cable. The network splitter has two LEDs for diagnostic purposes.

## Controls and indicators

- Power status LED
- Fault status LED
- Jumpers to configure tap-offs power behavior

## Interconnections

- Two system network connections for main network
- Two system network connection for network tap-offs
- External power supply input

## Certifications and Approvals

Safety	acc. to IEC 60065-98
Immunity	acc. to EN 55103-2
Emissions	acc. to EN 55103-1 / FCC-47 part 15B
EVAC (TÜV certified)	acc. to IEC 60849 / BS 5839-8

## Parts Included

Quantity	Component
1	LBB 4410/00 Network Splitter
1	Mounting bracket
1	Power supply connector

## Technical Specifications

### Electrical

Power consumption 3.9 W (network)

### External power supply

Voltage 24 to 56 VDC, 48 VDC nominal

Current 2.5 A maximum (5 A peak <2 s)

### Mechanical

Dimensions (H x W x D) 28.9 x 200 x 82.5 mm

Weight 0.3 kg

Mounting 2 screws in bracket

Color Charcoal

### Environmental

Operating temperature -5 °C to +45 °C

Storage temperature -20 °C to +70 °C

Humidity 15% to 90%

Air pressure 600 to 1100 hPa

## Ordering Information

LBB 4410/00 Network Splitter

LBB 4410/00

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Americas:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Asia-Pacific:**  
Bosch Security Systems Pte Ltd  
38C Jalan Pemimpin  
Singapore 577180  
Phone: +65 6319 3450  
Fax: +65 6319 3499  
apr.securitysystems@bosch.com  
www.boschsecurity.com

**Represented by**