

LBB 4410/00 Network Splitter

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Two current-limited network tap-offs
- ▶ Supports redundant network connection on main loop
- ▶ Can feed power from an external supply to the network
- ▶ Power 'ON' indication
- ▶ Fault indication

The network splitter is used in a network to provide two branches from the main cable run. It can use an external DC power supply, or it can use the power supply from the network controller. The unit automatically switches to the local power supply unit when it is connected to it, reducing the power drain on the main network. The network splitter can also function as a repeater, effectively extending the length of the main network another 50 meters.

Functions

The splitter inserts Praesideo units connected to a tap-off into the main network, however without the redundancy of the main loop. The maximum current supplied for each of the two tap-offs is separately selectable. External power from the local supply is used only for the tap-offs, and is not fed into the main system cable. The network splitter has two LEDs for diagnostic purposes.

Controls and indicators

- Power status LED
- Fault status LED
- Jumpers to configure tap-offs power behavior

Interconnections

- Two system network connections for main network

- Two system network connection for network tap-offs
- External power supply input

Certifications and approvals

Safety	acc. to IEC 60065-98
Immunity	acc. to EN 55103-2
Emissions	acc. to EN 55103-1 / FCC-47 part 15B
EVAC (TÜV certified)	acc. to IEC 60849 / BS 5839-8

Region	Certification
Europe	CE
Poland	CNBOP

Parts included

Quantity	Component
1	LBB 4410/00 Network Splitter
1	Mounting bracket
1	Power supply connector

Technical specifications

Electrical

Power consumption	3.9 W (network)
External power supply	
Voltage	24 to 56 VDC, 48 VDC nominal
Current	2.5 A maximum (5 A peak <2 s)

Mechanical

Dimensions (H x W x D)	28.9 x 200 x 82.5 mm
Weight	0.3 kg
Mounting	2 screws in bracket
Color	Charcoal

Environmental

Operating temperature	-5 °C to +45 °C
Storage temperature	-20 °C to +70 °C
Humidity	15% to 90%
Air pressure	600 to 1100 hPa

Ordering information

LBB 4410/00 Network Splitter

Optical network splitter for tapping off two branches from the optical network cable run.

Order number **LBB4410/00**

Represented by:

Americas:

Bosch Security Systems, Inc.
12000 Portland Avenue South
Burnsville MN 55337, USA
Phone: +1-800-392-3497
Fax: +1-800-955-6831
audiosupport@us.bosch.com
www.boschsecurity.com

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com