

## CCSE-CMS Chairperson device short mic, black

### CCS 700



The CCS 700 Discussion System is suitable for use in small meetings and conference venues with a limited number of participants.

The CCSE-CMS Chairman Units are equipped with enhanced functionality that enables the user to take the role of chairman in a conference or meeting. The unit has a fixed microphone with flexible stem of shorter length. Two headphone sockets can be used in situations with excessive background noise.

#### Functions

##### Priority button for chairman microphone

In addition to the 'microphone on' button the chairman units feature a 'chairman priority' button. When pressed the priority button causes all currently active delegate microphones to be temporarily or permanently muted.

##### Optional chime tone facility for preceding chairman announcements

A sliding switch is available on the rear of the CCSE-CU which can be used to activate the chime tone to precede chairman priority calls.

##### Built-in loudspeaker

Loudspeaker volume is set centrally at the Control Unit for all chairman and delegate units. To prevent acoustic feedback, the built-in loudspeaker is automatically muted when the microphone is on.

##### Two headphone sockets

Two 3.5 mm (0.14 in) stereo headphone sockets (wired for mono) allow two pairs of headphones to be connected so two delegates can simultaneously

- ▶ Priority button for chairman microphone
- ▶ Optional chime tone facility for preceding chairman announcements
- ▶ Modern, unobtrusive styling to match the CCSE-DS Delegate Units
- ▶ Microphone with flexible stem of shorter length and light ring
- ▶ Two headphone sockets

use the unit. It is also possible to connect a tape recorder to one headphone socket, and use the other headphone socket to listen to the proceedings.

##### Built-in volume control for headphones

The headphone volume level can be adjusted by means of a thumbwheel on the unit for maximum comfort.

##### Controls and Indicators

- Microphone on/off button
- Chairman priority button
- Rotary volume control for adjusting headphone volume
- Loudspeaker, automatically muted when microphone is on
- Microphone 'on' indicator (red LED)
- Light ring indicator on microphone stem, lights up red when microphone is on

##### Interconnections

- 1 x 2 m (78.7 in) cable terminated with an 8-pin male connector, for loop-through connection to other delegate or chairman units
- 1 x 8-pin circular female connector for loop-through connection to other delegate or chairman units
- 2 x 3.5 mm (0.14 in) stereo headphone sockets

#### Installation/configuration notes

This is a professional product that should be installed, used and maintained by trained professionals only.

## Parts included

Quantity	Component
1	CCSE-CMS Chairperson device short mic, black

## Technical specifications

### Electrical

Nominal acoustic input	85 dB SPL
Frequency response	200 Hz to 12.5 kHz

### Mechanical

Dimensions (without microphone) (H x W x D)	54 x 136 x 138 mm
Length of the microphone from the base of the stem	318 mm
Weight	1.2 kg
Mounting	Tabletop
Color	Charcoal

### Environmental

Operating temperature	-5 °C to +55 °C
Storage temperature	-40 °C to +70 °C

## Ordering information

### CCSE-CMS Chairperson device short mic, black

Chairperson device short mic, black base

Order number **CCSE-CMS | F.01U.315.103**

#### Represented by:

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
[www.boschsecurity.com/xc/en/contact/](http://www.boschsecurity.com/xc/en/contact/)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**Germany:**  
Bosch Sicherheitssysteme GmbH  
Robert-Bosch-Platz 1  
D-70839 Gerlingen  
[www.boschsecurity.com](http://www.boschsecurity.com)

**North America:**  
Bosch Security Systems, LLC  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
[www.boschsecurity.com](http://www.boschsecurity.com)

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
[www.boschsecurity.com/xc/en/contact/](http://www.boschsecurity.com/xc/en/contact/)  
[www.boschsecurity.com](http://www.boschsecurity.com)