

GB Motor bells, 24V

www.boschsecurity.com



BOSCH
Invented for life



- ▶ 24 VDC, polarized to allow for electrical supervision
- ▶ Sound level at 10 ft. (3.05 m) = 96 dBA
- ▶ Mounts to standard 4-inch square electrical box
- ▶ Red metal 6-inch or 10-inch gong
- ▶ ANSI/UL 464 Listed

Certifications and approvals

Region	Regulatory compliance/quality marks	
USA	UL	UL 464, Audible Signaling Devices for Fire Alarm and Signaling Systems, Including Accessories
	CSFM	see www.boschsecurity.com (the Bosch website)

Technical specifications

Electrical

Current draw	100 mA
Voltage	24 VDC

Environmental

Temperature, operating	+32°F to +120°F (0°C to +49°C)
------------------------	--------------------------------

Mechanical

Color	Red
Dimensions	
Gong (diameter)	6 in. or 10 in.
Mechanism (base)	4.6 in. (11.7 cm) square
Sound level at 10 ft. (3.05 m)	96 dBA
Packaging	
GB10-24	
gross	4.14 lb. (1.88 kg)
net	3.73 lb. (1.69 kg)
GB6-24	
gross	2.1 lb. (0.953 kg)
net	1.75 lb. (0.796 kg)

Trademarks

All hardware/software product names used in this document are likely to be registered trademarks and must be treated accordingly.

Ordering information

GB10-24 Bell, 24V 10", red

Red motor bell, 10-inch (25.4 cm) diameter, 24 volt
Order number **GB10-24**

GB6-24 Bell, 24V 6", red

Red motor bell, 6-inch (15.24 cm) diameter, 24 volt
Order number **GB6-24**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
emea.securitysystems@bosch.com
emea.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Germany
www.boschsecurity.com

North America:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.us

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia