

HS4-24MCW-FR Multi-candela Horn Strobe (red)

www.boschsecurity.com



BOSCH
Invented for life



- ▶ 24 VDC, filtered or FWR
- ▶ Four selectable candela settings - 15 cd, 30 cd, 75 cd, or 110 cd
- ▶ Continuous or temporal (Code 3) horn tones
- ▶ Selectable dBA settings (high, medium, or low)
- ▶ Easy wall mounting on a variety of back boxes

This red Wheelock horn strobe is UL Listed for indoor wall-mount applications and provides four selectable candela settings (15 cd, 30 cd, 75 cd, or 110 cd). The horns provide a continuous horn tone or temporal (Code 3) horn tone with three selectable sound output (dBA) settings for each tone. The temporal tone can be synchronized by using an SM (single) or DSM (dual) Synchronization Module or a compatible control panel. The strobe and horn circuits can be operated independently.

Certifications and approvals

Cooper Wheelock, Inc. holds these Listings and Approvals:

Region	Certification	
USA	UL	ULSZ: Audible Signal Appliances (UL464), UUKC: Signaling Appliances and Equipment for the Hearing Impaired (UL1971)
	CSFM	see our website

Installation/configuration notes

Compatible Products

The following products are compatible with the HS4 Horn Strobes:

Category	Product ID	Product Description
Control Panels	D7022 ¹	Conventional FACP
	D7024 ²	Addressable FACP
	D7024	Conventional FACP
	D8024 ¹	Analog FACP
	D9124 ¹	Addressable FACP
	D10024A ¹	Analog FACP
	FPA-1000	Analog Addressable FACP
	FPD-7024 ²	Addressable FACP
Modules	FPD-7024	Conventional FACP
	SM-12/24-R	Synchronization module (red)
	DSM-12/24-R	Dual synchronization module (red)

¹ For synchronization, use the SM or DSM Synchronization Modules. The synchronization module must be set for 24 VDC operation. When used, the D7022 must be set for 24 VDC operation.

² When used with a D7039 Multiplex Expansion Module, the D7024 and FPD-7024 become addressable fire alarm control panels (FACPs).

Mounting Considerations

Indoor Applications

Mount these HS4 Horn Strobes on the indicated back boxes for the indicated applications:

	Conduit Applications	Surface Mounted	Flush Mounted
Double-gang			•
Four-inch square			•
100-mm European			•
IOB ¹	•	•	
SHBB-R	•	•	

¹ Although the IOB Back Box is an indoor or outdoor box, the HS4 Series Horn Strobes are only UL Listed for indoor applications.

Wiring

Notice

The horn circuit of these horn strobes can be used on coded systems where the applied voltage is cycled on and off, but the strobe circuit cannot.

The input terminals accept wires with diameters between 18 AWG and 12 AWG (ISO 0.75 mm² and 4 mm²).

Parts included

Quant.	Component
1	Horn strobe
1	Hardware pack
1	Literature pack

Technical specifications

Electrical

Current (maximum) VDC

Audible only:	High dBA: 110 mA Medium dBA: 68 mA Low dBA: 27 mA
Strobe only:	15 cd: 60 mA 30 cd: 92 mA 75 cd: 165 mA 110 cd: 220 mA

Current (maximum) VFWR

Audible only:	High dBA: 94 mA Medium dBA: 50 mA Low dBA: 41 mA
Strobe only:	15 cd: 102 mA 30 cd: 155 mA 75 cd: 253 mA 110 cd: 347 mA
Voltage (input)	24 VDC nominal filtered or FWR; 16 VDC to 33 VDC

Environmental

Relative Humidity:	Up to 95%, non-condensing
Temperature (Operating):	+32°F to +120°F (0°C to +49°C)

Mechanical

Candela Selections:	15 cd, 30 cd, 75 cd, or 110 cd
Dimensions (H x W x D):	4.125 in. x 4.125 in. x 1.25 in. (10.5 cm x 10.5 cm x 3.2 cm)
Material:	Molded plastic enclosure incorporating a Xenon flashtube and Lexan lens

Horn Ratings at 24 VDC

Continuous Horn

Reverberant dBA at 10 ft (3 m) per UL464:	High: 91 dBA Medium: 88 dBA Low: 83 dBA
---	---

Temporal (Code 3) Horn

Reverberant dBA at 10 ft (3 m) per UL464:	High: 87 dBA Medium: 84 dBA Low: 79 dBA
---	---

Notice

The sound output for the Temporal (Code 3) mode is rated lower than in Continuous mode because the time that the horn is off is averaged into the sound output rating. When the horn produces a tone in Temporal mode, its sound pressure is the same as the Continuous mode.

Trademarks

All hardware and software product names used in this document are likely to be registered trademarks and must be treated accordingly.

Ordering information

HS4-24MCW-FR Multi-candela Horn Strobe (red)

Red, 24 VDC device with four selectable candela settings (15 cd, 30 cd, 75 cd, or 110 cd), three selectable sound output (dBA) settings, and a choice of continuous or temporal (Code 3) horn tone
Order number **HS4-24MCW-FR**

Accessories

DBB-R Steel Back Box (red)

8.6 cm (3.375 in.) square, 5.6 cm (2.1875 in.) deep
Order number **DBB-R**

IOB-R Indoor or Outdoor Back Box (red)

13.3 cm (5.25 in.) square, 6.7 cm (2.625 in.) deep
Order number **IOB-R**

ISP2-R Surface Adapter (red)

13.3 cm (5.25 in.) square, 3 cm (1.1875 in.) deep
Order number **ISP2-R**

ISP2-W Surface Adapter (white)

13.3 cm (5.25 in.) square, 3 cm (1.1875 in.) deep
Order number **ISP2-W**

RP-R Retrofit Plate (red)

20.3 cm (8 in.) high, 14.9 cm (5.875 in.) wide.
Not Available.
Order number **RP-R**

SBB-R Surface-mount Back Box (red)

14 cm (5.5 in.) x 14.2 cm (5.6 in.) x 9.1 cm (3.6 in.)
Order number **SBB-R**

SBB-W Surface-mount Back Box (white)

14 cm (5.5 in.) x 14.2 cm (5.6 in.) x 9.1 cm (3.6 in.)
Order number **SBB-W**

SFP-R Semi-flush Plate (red)

15.2 cm (6 in.) square by 0.8 cm (0.3125 in.) thick
Order number **SFP-R**

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com