

FCP-320/FCH-320 Conventional Automatic Fire Detectors



The FCP-320/FCH-320 Series Conventional Automatic Fire Detectors set new standards in fire detection technology through a combination of optical, thermal and chemical (gas) sensors and intelligent evaluation electronics. Their most impressive feature is their ability to prevent false alarms, as well as speed and accuracy of detection.

The enhanced operating voltage range of 8.5 V DC up to 30 V DC and the two variants with 820 Ω alarm resistor or 470 Ω alarm resistor enables the detector application with nearly all conventional fire panels.

System overview

Operating mode	Detector type			
	FCP-OC320 / FCP-OC320-R470	FCP-OT320 / FCP-OT320-R470	FCP-O320 / FCP-O320-R470	FCH-T320 / FCH-T320-FSA / FCH-T320-R470
Combined	x	x	-	-
Optical (scattered light measurement)	x	x	x	-
Thermal max.	-	x	-	x

V d S

- ▶ High reliability of detection thanks to evaluation electronics
- ▶ Active adjustment of the threshold (drift compensation) if the optical sensor becomes dirty
- ▶ Activation of a remote external detector alarm display possible
- ▶ Mechanical removal lock (can be activated/deactivated)
- ▶ Dust-repellent labyrinth and cap construction

Thermal differential	-	x	-	x
Chemical (gas measurement)	x	-	-	-

Functions

The FCP-OC320 and FCP-OT320 Multisensor Detectors each combine two detection principles. All sensor signals are analyzed continually by the internal evaluation electronics and are linked with each other. If a signal combination fits the detector's programmed code field, an alarm is automatically triggered. By linking the sensors, the combined detectors can also be used in places where work carried out gives rise to light smoke, steam or dust.

Optical sensor (smoke sensor)

The optical sensor uses the scattered-light method. An LED transmits light to the measuring chamber, where it is absorbed by the labyrinth structure. In the event of a fire, smoke enters the measuring chamber and the smoke particles scatter the light from the LED. The amount of light hitting the photo diode is converted into a proportional electrical signal.

Thermal sensor (temperature sensor)

A thermistor in a resistance network is used as a thermal sensor; an analog-digital converter measures the temperature-dependent voltage at regular intervals.

When the maximum temperature of 54°C is exceeded (thermal maximum), or if the temperature rises by a defined amount within a specified time (thermal differential), the temperature sensor triggers the alarm status.

Chemical sensor (CO gas sensor)

The main function of the gas sensor is to detect carbon monoxide (CO) generated as a result of a fire, but it will also detect hydrogen (H) and nitrous monoxide (NO). The sensor signal value is proportional to the concentration of gas. The gas sensor delivers additional information to effectively suppress deceptive values.

Depending on the service life of the gas sensor, the OC 320 detector switches off the C sensors after five years of operation. The detector will continue to function as an O detector. The detector should then be exchanged immediately in order to be able to keep using the higher reliability of detection of the OC detector.

Special features

Detector type	Drift compensation	
	Optical unit	Gas sensor
FCP-OC320 FCP-OC320-R470	x	x
FCP-OT320 FCP-OT320-R470	x	--
FCP-O320 FCP-O320-R470	x	--
FCH-T320 FCH-T320-R470 FCH-T320-FSA	--	--

The detectors comply with:

Detector type	EN54-5:2000/ A1:2002	EN54-7:2000/ A1:2002/A2:2006
FCP-OC320		●
FCP-OC320-R470		●
FCP-OT320	●	●
FCP-OT320-R470	●	●
FCP-O320		●
FCP-O320-R470		●
FCH-T320	●	
FCH-T320-R470	●	

FCH-T320-FSA



Regulatory information

Region	Regulatory compliance/quality marks	
Morocco	CMIM	FCP-320
	CMIM	MSS300
Europe	CPR	0786-CPR-20351 FCP-O320_FCP-O320-R470
	CPR	0786-CPR-20352 FCP-OT320_FCP-OT320-R470
	CPR	0786-CPR-20353 FCH-T320_FCH-T320-R470
	CPR	0786-CPR-20355 FCP-OC320_FCP-OC320-R470
	CPR	0786-CPR-20354 FCH-T320-FSA
Germany	VdS	G 208001 FCP-O320_-R470
	VdS	G 208002 FCP-OT320_-R470
	VdS	G 208003 FCH-T320_-R470
	VdS	G 208004 FCH-T320-FSA
	VdS	G 208005 FCP-OC320_-R470
Europe	CE	FCP-/FCH-320
	CE	MSR 320
	CPD	0786-CPD-20354 FCH-T320-FSA

Installation/configuration notes

- Up to 32 detectors can be connected per primary line
- Maximum cable length: 1000 m, for J-Y(St) Y n x 2 x 0.6/0.8
- Country-specific standards and guidelines must be observed during the planning phase
- The detector can be painted (cap and base) and thereby adapted to the surrounding colour scheme; note the information in the Painting Instructions (Document Number F.01U.089.231)

Installation/configuration notes in accordance with VdS/VDE/DIBt

- Planning for multisensor detectors follows the guidelines for optical detectors, unless a specific VdS planning guideline is available (see DIN VDE 0833 Part 2 and VDS 2095)
- The OC and OT types are planned using the guidelines for optical detectors if operated as optical detectors or as combined detectors; see DIN VDE 0833 Part 2 and VDS 2095

- When planning fire barriers according to DIBt, you have to use the FCH-T320-FSA; its characteristic curve corresponds to category A1R

Technical specifications

Electrical

Operating voltage	8.5 V DC to 30 V DC
Current consumption	< 0.12 mA
Alarm output	Increase in current (alarm resistance 820 Ω or 470 Ω)
Indicator output	Open collector connects 0 V in the event of an alarm over 3.92 kΩ

Mechanics

Individual display	LED red
Dimensions	
• Without base	Ø 99.5 x 52 mm
• With base	Ø 120 x 63.5 mm
Housing material	Plastic, ABS
Housing color	White, similar to RAL 9010, matt finish
Weight without/with packaging	Approx. 80 g / approx. 120 g
• FCP-OC320 / FCP-OC320-R470	Approx. 85 g / approx 130 g

Environmental conditions

Protection class as per EN 60529	IP 41, IP 43 with FAA-420-SEAL or MSC 420
Permissible relative humidity	95% (non-condensing)
Permissible air speed	20 m/s
Permissible operating temperature	-20 °C to +50 °C
• FCP-O320 / FCP-O320-R470	-20 °C to +65 °C
• FCP-OC320 / FCP-OC320-R470	-10 °C to +50 °C

Limits

Heed local guidelines. They overrule the following limits.

Monitoring area	Max. 120 m ² (Heed local guidelines!)
-----------------	--

• FCH-T320 / -R470 / -FSA	Max. 40 m ² (Heed local guidelines!)
Maximum installation height	16 m (Heed local guidelines!)
• FCH-T320 / -R470 / -FSA	6 m (Heed local guidelines!)

Special features

Response sensitivity	
• Optical part (in line with EN 54-7)	FCP-OC320 / FCP-OC320-R470 < 0.23 dB/m FCP-OT320 / FCP-OT320-R470 < 0.19 dB/m FCP-O320 / FCP-O320-R470 < 0.16 dB/m
• Thermal maximum part	>54 °C
• Thermal rate-of-rise part (in line with EN 54-5)	FCH-T320 / FCH-T320-R470: A2R FCH-T320-FSA: A1R
• Chemical part	In ppm range
Color code	
• FCP-OC320 / FCP-OC320-R470	Blue ring
• FCP-OT320 / FCP-OT320-R470	Black ring
• FCP-O320 / FCP-O320-R470	No marking
• FCH-T320 / FCH-T320-R470 / - FSA	Red ring

Ordering information

FCP-O320 Smoke detector optical

conventional technology, with 820 Ohm alarm resistor
Order number **FCP-O320 | F.01U.026.293**

FCP-OT320 Multisensor detector optical/thermal

conventional technology, with 820 Ohm alarm resistor
Order number **FCP-OT320 | F.01U.026.295**

FCP-OC320 Multisensor detector optical/chemical

conventional technology, with 820 Ohm alarm resistor
Order number **FCP-OC320 | F.01U.026.292**

FCP-OC320-R470 Multisensor detector optical/chemical

conventional technology, with 470 Ohm alarm resistor
Order number **FCP-OC320-R470 | F.01U.029.867**

FCP-OT320-R470 Multisensor detector optical/thermal

conventional technology, with 470 Ohm alarm resistor
Order number **FCP-OT320-R470 | F.01U.029.862**

FCP-O320-R470 Smoke detector, optical

conventional technology, with 470 Ohm alarm resistor
Order number **FCP-O320-R470 | F.01U.029.857**

FCH-T320 Heat detector, rate-of-rise

conventional technology, thermal differential/thermal maximum detector, with 820 Ohm alarm resistor
Order number **FCH-T320 | F.01U.026.291**

FCH-T320-R470 Heat detector

thermal differential/thermal maximum detector, conventional technology, with 470 Ohm alarm resistor
Order number **FCH-T320-R470 | F.01U.029.861**

FCH-T320-FSA Heat detector, DIBt protection closures

thermal differential/thermal maximum detector, conventional technology, with 820 Ohm alarm resistor
Order number **FCH-T320-FSA | F.01U.026.294**

Accessories**MS 400 B Detector base with Bosch logo**

Bosch-branded detector base for surface mounted and flush-mounted cable feed
Order number **MS 400 B | F.01U.215.139**

MS 400 Detector base

Detector base for surface mounted and flush-mounted cable feed, not branded.
Order number **MS 400 | 4.998.021.535**

FAA-420-SEAL Damp room seal, 10 pcs

Damp room seal
Delivery unit is 10.
Order number **FAA-420-SEAL | F.01U.215.142**

MSR 320 Base with relay, conventional

with a change-over relay (Form C)
Order number **MSR 320 | 4.998.114.565**

MSC 420 Base extension with damp room sealing

Extension for detector bases with surface-mounted cable feed
Order number **MSC 420 | 4.998.113.025**

MSS 300 Base sounder white

Control via C-point of the detector
Order number **MSS 300 | 4.998.025.371**

MSS300-WH-EC Base sounder, white

Control through fire panel via interface
Order number **MSS300-WH-EC | 4.998.120.501**

FAA-420-RI-DIN Remote indicator for DIN application

For applications where the automatic detector is not visible, or mounted in false ceilings/floors.
This version complies with DIN 14623.
Order number **FAA-420-RI-DIN | F.01U.289.620**

FAA-420-RI-ROW Remote indicator

For applications where the automatic detector is not visible, or mounted in false ceilings/floors.
Order number **FAA-420-RI-ROW | F.01U.289.120**

FMX-DET-MB Mounting bracket

Mounting bracket for installation in false floors
Order number **FMX-DET-MB | 2.799.271.257**

WA400 Wall bracket

Console for DIBt compliant mounting of detectors above doors etc., including detector base
Order number **WA400 | 4.998.097.924**

MH 400 Heating element

usable at locations where the functional safety of the detector might be impaired by condensation
Order number **MH 400 | 4.998.025.373**

SK 400 Protective cage

prevents damage
Order number **SK 400 | 4.998.025.369**

SSK400 Dust protection, 10pcs

Protective dust cover for automatic point type detectors.
Delivery unit is 10.
Order number **SSK400 | 4.998.035.312**

TP4 400 Label plate small

Support plate for detector identification.
Delivery unit is 50.
Order number **TP4 400 | 4.998.084.709**

TP8 400 Label plate large

Support plate for detector identification, large.
Delivery unit is 50.
Order number **TP8 400 | 4.998.084.710**

Services**EWE-FPTDT-IW 12 mths wrty ext Fire Point Detector**

12 months warranty extension
Order number **EWE-FPTDT-IW | F.01U.360.736**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 40 2577 284
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Tel.: +49 (0)89 6290 0
Fax: +49 (0)89 6290 1020
de.securitysystems@bosch.com
www.boschsecurity.com

North America:
Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com