

FNS-320 Beacons Conventional

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Compact, robust and maintenance-free
- ▶ Reliable, bright light, and long-lived with Xenon flash tubes
- ▶ For operating voltage 12 V DC and 24 V DC
- ▶ Can be used in adverse environmental conditions

The FNS-320 Beacons are universally employable optical signaling devices.

Functions

The beacon lamp is mounted in the upper, clear part of the device. When activated via the fire panel, it flashes with a flash rate of once a second. The connections are protected against reverse polarity.

Certifications and approvals

Region	Certification	
Europe	CE	FNS-320-SRD, FNS-320-SYE, FNS-320-SWH, FNS-320-SGR
Poland	CNBOP	1229/2012 FNS-320-SRD

Installation/configuration notes

- The device is not certified to EN 54-23. It is not suitable for fire alarm use within the EU.
- The device is suitable for indoor and outdoor use. (Outdoor use only with appropriate cable fittings. Not included in delivery.)
- The upper part is fixed to the base by a bayonet lock.
- The lens has screw threads and is also secured against removal by a security screw.

- The device can be connected to the following panels:
 - FPA-5000 / FPA-1200 with NZM 0002 A or FLM-420-NAC
 - BZ 500 LSN, UEZ 1000 LSN, UEZ 2000 LSN, UGM 2020

Parts included

Quant.	Component
1	Signaling device in red, clear, amber or green
1	Mounting base, red, surface mounting

Technical specifications

Electrical

Operating voltage	9 V DC to 30 V DC
Current consumption	
• 24 V	88 mA
• 12 V	185 mA

Mechanics

Housing material	ABS V0 + PC
Base color	Red, RAL 3001

Dimensions (Ø x H)	93 mm x 121 mm
Weight	180 g

Environmental conditions

Protection class as per EN 60529	IP 21C (IP 65)*
Permissible operating temperature	-20 °C to +70 °C
Permissible rel. humidity	

*Manufacturers specification, not third party verified

Special features

Light output	10 cd (1.25 J)
Flash rate	1Hz

Ordering information

FNS-320-SRD Beacon Red, Surface Mounting

for local visual signaling
Order number **FNS-320-SRD**

FNS-320-SGR Beacon Green, Surface Mounting

for local visual signaling
Order number **FNS-320-SGR**

FNS-320-SYE Beacon Amber, Surface Mounting

for local visual signaling
Order number **FNS-320-SYE**

FNS-320-SWH Beacon Clear, Surface Mounting

for local visual signaling
Order number **FNS-320-SWH**

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com