

IIR-50850-SR Illuminator, 850nm, short range



- ▶ Integrated adjustable photocell
- ▶ Adjustable IR intensity
- ▶ Interchangeable beam pattern diffusers to match beam to camera
- ▶ Telemetry input and photocell output for external switching
- ▶ Self-cleaning lens coating technology

Regulatory information

Region	Regulatory compliance/quality marks
Europe	CE
Great Britain	UKCA
USA	UL

Installation/configuration notes

Use only one of these three Power supply units with this product:

- PSU-IIR-35
- PSU-IIR-60
- PSU-IIR-100

Parts included

Quantity	Component
1	IR illuminator with bracket
5	Beam pattern diffusers
1	Installation Guide

Technical specifications

Power	
Power supply	12 to 32 VDC

Power	
Power consumption	13 W

Optical	
Wavelength	850 nm or 940 nm
IR control	Adjustable IR intensity (10% to 100%)
Day/night switch	Photocell, sensitivity adjustable (20 lx to 70 lx)
Beam angles	10°, 20°, 30°, 60°, 80°, and 95°

Range 850 nm		
Beam pattern diffuser	Achievable Distance*	HFOV
10°	156 m (510 ft)	27 m (89 ft)
20°	106 m (348 ft)	37 m (123 ft)
30°	78 m (255 ft)	42 m (137 ft)
60°	49 m (162 ft)	57 m (187 ft)
80°	35 m (116 ft)	59 m (195 ft)
95°	25 m (81 ft)	54 m (177 ft)

Range 940 nm		
Beam pattern diffuser	Achievable Distance*	HFOV
10°	95 m (313 ft)	17 m (55 ft)

Range 940 nm		
Beam pattern diffuser	Achievable Distance*	HFOV
20°	57 m (186 ft)	20 m (65 ft)
30°	46 m (151 ft)	25 m (81 ft)
60°	28 m (93 ft)	33 m (107 ft)
80°	21 m (70 ft)	36 m (117 ft)
95°	14 m (46 ft)	31 m (101 ft)

* Actual illumination distance achieved is dependent on camera and lens characteristics.

Mechanical	
Housing	Robust anodized aluminum extrusion, black
Front window	Polycarbonate high transmittance (vandal-resistant) with self-cleaning technology
Mount	Black powder coated stainless steel U-bracket (adjustable with M6 socket-head wrench)
Cable	3 m (9 ft)
Dimensions (W x H x D)	110 x 68 x 75 mm (4.33 x 2.68 x 2.95 in)
Bracket dimensions (W x H x D)	110 x 125 x 35 mm (4.33 x 4.92 x 1.38 in)
Weight	750 g (1.6 lbs)
Bracket weight	0.2 kg (0.44 lbs)

Environmental	
Operation Temperature Range	-50 °C to +50 °C (-58 °F to +122 °F)
Protection	IP66

Ordering information

IIR-50850-SR Illuminator, 850nm, short range

Short range IR illuminator

850 nm

Order number **IIR-50850-SR**

Accessories

IIR-MNT-SLB Bracket for illuminator, single L, black

Illuminator single L-bracket, black

Order number **IIR-MNT-SLB**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Tel.: +49 (0)89 6290 0
Fax: +49 (0)89 6290 1020
de.securitysystems@bosch.com
www.boschsecurity.com

North America:
Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
www.boschsecurity.com/xc/en/contact/
www.boschsecurity.com

IIR-MNT-DLB Bracket for illuminator, double L, black

Illuminator double L-bracket, black

Order number **IIR-MNT-DLB**

IIR-MNT-TLB Bracket for illuminator, triple L, black

Illuminator triple L-bracket, black

Order number **IIR-MNT-TLB**

IIR-MNT-PMB Bracket for illuminator, pole mount

Illuminator pole mount bracket, black

Order number **IIR-MNT-PMB**

PSU-IIR-35 Power supply, 100-240VAC/24VDC, 1.25A

Constant Voltage, 24 VDC, 35W power supply designed for LED lighting applications. 100-240VAC in, 1.46A out. Aluminum case rated IP67.

Order number **PSU-IIR-35**

PSU-IIR-60 Power supply, 100-240VAC/24VDC, 2.5A

Constant Voltage, 24 VDC, 60W power supply designed for LED lighting applications. 100-240VAC in, 2.5A out. Aluminum case rated IP67.

Order number **PSU-IIR-60**

PSU-IIR-100 Power supply, 100-240VAC/24VDC, 4.2A

Constant Voltage 24 VDC, 100W power supply designed for LED lighting applications. 100-240VAC in, 4.16A out. Aluminum case rated IP67.

Order number **PSU-IIR-100**

Services

EWE-IIR850-IW 12 mths wrty ext IR Illuminator 850 nm

12 months warranty extension

Order number **EWE-IIR850-IW**