ISN-CMINI-10D Miniature Contacts with Thin Magnet (9.5 mm)

www.boschsecurity.com





- ► Closed loop
- ▶ Ideal for tight-fitting applications
- ▶ Versatile

The contacts are available in brown or white. All models have a true miniature design and are shorter than compact design contacts. All models include a powerful, thin magnet. The magnet has a convex hole that allows flat head screws to fit flush. Use on window frames or door frames in tight-fitting applications.

Certifications and approvals

UL and

| Region | Certification | |
|--------|---------------|---|
| Europe | CE | 73/23/EEC and 93/68/EEC, EN50131: 1997, EN50131-6: 1997, EN60950: 2000, EN60335-1: 1994 +A1: 1996 Annex B |
| USA | UL | cULus: AMQV: Connectors and Switches (UL 634), AMQV7: Connectors and Switches Certified for Canada (ULC/ ORD-C634) |

Installation/configuration notes

Compatibility Information

All contact models are compatible with control panel models that accept contact inputs.

Parts included

| Quantity Per Package | Component |
|----------------------|-----------|
| 10 | Contacts |
| 10 | Magnets |

Technical specifications

Specifications for All Models

| Gap Width: | 12.7 mm (0.5 in.) |
|-----------------------------|--|
| Contact Dimensions: | 9.5 mm x 15.2 mm (0.375 in. x 0.6 in.) |
| Magnet Dimensions: | 9.5 mm x 3 mm (0.375 in. x 0.125 in.) |
| Wire Lead Type: | 0.8 mm (0.029 in.) 22 AWG, 7 stranded |
| Wire Lead Length: | 46 cm (18 in.) standard leads |
| Switch Configuration Type: | Single pole single throw (SPST) |
| Maximum Contact Resistance: | 150 μΩ (micro-ohm) |
| Minimum Breakdown Voltage: | 200 VDC |
| | |

| Insulation Resistance: | 10 ⁹ Ω |
|------------------------------|-------------------------------------|
| Electrostatic Cap: | 1.5 PF |
| Contact Capacity: | 3 VAC |
| Maximum Conductive Current: | 0.5 A |
| Maximum Voltage: | 30 V |
| Operating Temperature Range: | 7.2°C to -95.56°C (-45°F to -140°F) |

Package Information

ATTENTION! Each package contains ten contacts and ten magnets.

Ordering information

Brown Miniature Contact with Thin Magnet

Brown recessed contact with 9.5 mm (0.375 in.) diameter. Includes a thin magnet. Package contains ten contacts and ten magnets.

Order number ISN-CMINI-10DB

White Miniature Contact with Thin Magnet

White recessed contact with 9.5 mm (0.375 in.) diameter. Includes a thin magnet. Package contains ten contacts and ten magnets.

Order number ISN-CMINI-10DW

Represented by:

Americas:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0996
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 800020
5617 BA Eindhoven, The Netherlands
Phone: +31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd. 201 Building, No. 333 Fuquan Road North IBP Changning District, Shanghai 200335 China Phone 486 21 22181111 Fax: 486 21 2218398 www.bossbecurity.com.cn

Robert Bosch Ltda Security Systems Division Via Anhanguera, Km 98 CEP 13065-900 Campinas, Sao Paulo, Brazil Phone: +55 19 2103 2860

Campinas, Sao Paulo, Brazil Phone: +55 19 2103 2860 Fax: +55 19 2103 2862 latam.boschsecurity@bosch.com www.boschsecurity.com

America Latina: