

LECTUS select



The LECTUS select line consists of two different reader variants, one with keypad and one without keypad. The series is available in black and in white color.

All reader variants, can be flush-mounted or, when using the optional mounting frame, surface-mounted. To detect unauthorized disassembly, the readers have sabotage detection.

The readers do support MIFARE DESFire EV1 and EV2 as well as LEGIC Advant.

The reader series has an RS485 interface and offers two protocol variants, OSDP including OSDPv2 secure channel or phg_crypt.

When operating the reader in RS485/OSDP mode, up to eight readers can be connected to a respective controller, e.g. AMC2-4R4. The reader address can be set via four DIP-switches.

The phg_crypt protocol is a proprietary secure protocol which can be used in third-party installations such as “Matrix”, offered by Bosch Energy and Building Solutions. This protocol is not supported by the current AMC2 controllers.

Three LED indicators and a beeper give clear feedback to the user during operation.

The reader is IP54 rated.

Certifications and approvals

Region	Regulatory compliance/quality marks
Europe	CE
Global	RoHS



- ▶ Compact design
- ▶ Easy installation
- ▶ Sabotage monitoring
- ▶ Numbers and symbols backlit
- ▶ Three status LEDs

Installation/configuration notes

Software compatibility

The readers that support OSDP can be used with BIS and AMS software and support per default the following technologies:

- LEGIC Advant
- MIFARE DESFire EV1 & EV2

The readers with phg_crypt can be configured with, e.g. MATRIX access control system.

Technical specifications

Mechanical

Dimension (H x W x D) (mm)	88 x 101 x 35 mm (uninstalled) 88 x 101 x 21 mm (installed)
Dimension (H x W x D) (in)	3,5 x 4,0 x 1,4 in. (uninstalled) 3,5 x 4,0 x 0,83 in (installed)
Color	White/silver Black/silver
Material	Plastic
Mounting type	Flush-mounted
Weight (g)	137 g 139 g
Weight (lb)	0,302 lb 0,306 lb

Environmental

Usage	Indoor; Outdoor
-------	-----------------

Operating temperature (°C)	-25 - 60 °C
Operating temperature (°F)	-13 - 140 °F
Degree of protection (IEC 60529)	IP54

Electrical

Operating voltage (VDC)	8 - 30 VDC
Power consumption (VA)	3,50 VA maximum (2,5 VA typically)

Operation

Audible indication	Yes
Credential type	Cards/keyfobs/tokens; PIN
Keypad	Yes No
Optical indication	Yes
Software compatibility	Building Integration System (BIS) Access Management System (AMS) Third-party software (e.g. MATRIX access system, for readers with phg_crypt)
Reading technology	LEGIC prime* ¹ LEGIC advant MIFARE Classic* ¹ MIFARE DESFire EV1 & EV2 ISO14443A (CSN / UID)* ¹ ISO15693 (CSN / UID)* ¹
Reading distances	<ul style="list-style-type: none"> • LEGIC prime: card approx. 65 mm maximum, key fob 40 mm maximum • LEGIC advant: card approx. 25 mm maximum, key fob 20 mm maximum • MIFARE classic : card approx. 40 mm maximum, key fob 30 mm maximum • MIFARE DESFire EV1: card approx. 10 mm maximum, key fob 10 mm maximum

*¹ require specific configuration with OSDP protocol

Connectivity

Reader interfaces	RS485
Protocols and interfaces	OSDP; Phg_crypt

Ordering information

ARD-SELECT-BP Reader, phg_crypt, black

phg_crypt reader, for MIFARE classic, MIFARE EV1 & 2, Legic Prime and Advant, black, designed for flush-mount and IP54 rated for indoor and outdoor use.

Order number **ARD-SELECT-BP | F.01U.389.837**

ARD-SELECT-BPK Reader, phg_crypt, keypad, black

phg_crypt reader, with keypad, for MIFARE classic, MIFARE EV1 & 2, Legic Prime and Advant, black, designed for flush-mount and IP54 rated for indoor and outdoor use.

Order number **ARD-SELECT-BPK | F.01U.389.841**

ARD-SELECT-BO Reader, OSDP, black

OSDP reader for MIFARE EV1 & 2 and Legic Advant, black, designed for flush-mount and IP54 rated for indoor and outdoor use.

Order number **ARD-SELECT-BO | F.01U.389.839**

ARD-SELECT-BOK Reader, OSDP, keypad, black

OSDP reader, with keypad, for MIFARE EV1 & 2 and Legic Advant, black, designed for flush-mount and IP54 rated for indoor and outdoor use.

Order number **ARD-SELECT-BOK | F.01U.389.843**

ARD-SELECT-WP Reader, phg_crypt, white

phg_crypt reader, for MIFARE classic, MIFARE EV1 & 2, Legic Prime and Advant, white, designed for flush-mount and IP54 rated for indoor and outdoor use.

Order number **ARD-SELECT-WP | F.01U.389.838**

ARD-SELECT-WO Reader, OSDP, white

OSDP reader, for MIFARE EV1 & 2 and Legic Advant, white, designed for flush-mount and IP54 rated for indoor and outdoor use.

Order number **ARD-SELECT-WO | F.01U.389.840**

ARD-SELECT-WPK Reader, phg_crypt, keypad, white

phg_crypt reader, with keypad, for MIFARE classic, MIFARE EV1 & 2, Legic Prime and Advant, white, designed for flush-mount and IP54 rated for indoor and outdoor use.

Order number **ARD-SELECT-WPK | F.01U.389.842**

ARD-SELECT-WOK Reader, OSDP, keypad, white

OSDP reader, with keypad, for MIFARE EV1 & 2 and Legic Advant, white, designed for flush-mount and IP54 rated for indoor and outdoor use.

Order number **ARD-SELECT-WOK | F.01U.389.844**

Accessories

ARA-SELECT-SWA Wallmount Box Lectus Select, silver

Wallmount box for LECTUS select Reader Series, silver, fits to all readers with black front surface.

Order number **ARA-SELECT-SWA | F.01U.389.869**

ARA-SELECT-WWA Wallmount Box Lectus Select, white

Wallmount box for LECTUS select Reader Series, white

Order number **ARA-SELECT-WWA | F.01U.389.868**

Represented by:

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
emea.securitysystems@bosch.com
emea.boschsecurity.com

Germany:

Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Germany
www.boschsecurity.com

North America:

Bosch Security Systems, LLC
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.us

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia