

LVF-5005C-S4109 Varifocal lens, 4.1-9mm, 5MP, CS mount

www.boschsecurity.com



BOSCH

Invented for life



- ▶ High-quality optics
- ▶ Reliable, robust construction
- ▶ Focal length options

As surveillance cameras can now capture even higher picture resolutions through the use of HD sensor technology and advanced processing, the lenses also need to have an optical resolution that allows the camera to work at its optimal point.

This lens is designed to provide improved image resolution and sharpness, and better depth of field.

System overview

This lens comes with a standard CS mount for use with a variety of cameras.

The DC-iris control connection is a four-pin standard plug that fits directly into the camera's iris output. This lens delivers impressive optical quality due to its megapixel resolution, contrast reproduction, and coating.


The mechanical construction is designed to withstand both frequent iris control operations and the environmental stress of security installations. It provides long and reliable operation with no maintenance.

For flexible, high-quality, reliable lenses that match an HD camera's performance, this lens is the ideal solution.

Certifications and approvals

Region	Regulatory compliance/quality marks	
Europe	CE	LVF-5005C-S4109

Installation/configuration notes



4-pin iris connector

- Pin 1: Damping coil -
- Pin 2: Damping coil +
- Pin 3: Driving coil + (open)
- Pin 4: Driving coil -

Parts included

Quantity	Component
1	Unit

Technical specifications

LVF-5005C-S4109	
Maximum sensor format	1/1.8-inch
Optical resolution	5 Megapixels
Focal length	4.1 - 9 mm
Iris range	F1.6 to F8
Min object distance	0.3 m (1 ft)
Back focus distance (values in air)	12.72 mm (wide), 19.94 mm (tele)
Weight	130 g (0.29 lb)
Dimensions	Ø 62.9 mm (excluding focus and zoom knobs) x 66.6 mm (excluding flange)
Lens mount	CS
Angle of view (HxV)	63 x 47.1° Wide

LVF-5005C-S4109	
1/3-inch sensor 4:3	28.9 x 21.7° Tele
Angle of view (HxV) 1/3-inch sensor 16:9	72.8 x 40.7° Wide 33.3 x 18.8° Tele
Angle of view (HxV) 1/2.7-inch sensor 16:9	80.4 x 44.8° Wide 36.7 x 20.7° Tele
Angle of view (HxV) 1/1.8-inch sensor 16:9	100.9 x 55.9° Wide 45.7 x 25.7° Tele
Iris control	4-pin, DC control
Focus ctrl	manual
Zoom ctrl	manual
IR corrected	yes

Environmental	
- Operating Temperature	-10°C to +50°C (+14°F to +122°F)
- Storage Temperature	-40°C to +70°C (-40°F to + 158°F)
- Operating Humidity	Up to 93% non-condensing

Ordering information

LVF-5005C-S4109 Varifocal lens, 4.1-9mm, 5MP, CS mount
 Varifocal SR megapixel IR corrected lens with 1/1.8" sensor and CS-mount
 Order number **LVF-5005C-S4109**

Represented by:

Europe, Middle East, Africa:
 Bosch Security Systems B.V.
 P.O. Box 80002
 5600 JB Eindhoven, The Netherlands
 Phone: + 31 40 2577 284
 emea.securitysystems@bosch.com
 emea.boschsecurity.com

Germany:
 Bosch Sicherheitssysteme GmbH
 Robert-Bosch-Ring 5
 85630 Grasbrunn
 Germany
 www.boschsecurity.com

North America:
 Bosch Security Systems, LLC
 130 Perinton Parkway
 Fairport, New York, 14450, USA
 Phone: +1 800 289 0096
 Fax: +1 585 223 9180
 onlinehelp@us.bosch.com
 www.boschsecurity.us

Asia-Pacific:
 Robert Bosch (SEA) Pte Ltd, Security Systems
 11 Bishan Street 21
 Singapore 573943
 Phone: +65 6571 2808
 Fax: +65 6571 2699
 apr.securitysystems@bosch.com
 www.boschsecurity.asia