

LX Beacons Conventional

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Complies with EN54-23
- ▶ Up to 7.5 m coverage
- ▶ Variable flash rate
- ▶ Low current consumption
- ▶ LED technology

The LX Beacons are signaling devices for optical alarm.

Functions

The device has a unique lens design to achieve the required illumination specified by EN54-23. The flash rate as well as a reduced coverage volume can be set via DIP switch.

The ceiling device distributes the light in a cylindrical shape, the wall device in a cubical shape.

The device is designed for a variety of applications.

Certifications and approvals

Region	Regulatory compliance/quality marks	
Germany	VdS	G214067 Solista LX wall
	VdS	G214069 Solista LX ceiling
Europe	CPD	0333-CPD-075443 LX_Beacon_Ceiling_EN
	CPD	0333-CPD-075441 LX_Beacon_Wall_EN
Poland	CNBOP	2236/2014 Solista

Installation/configuration notes

- Can be connected to
 - LSN fire panels with NZM 0002 A or FLM-420-NAC
 - FPC-500 Conventional Fire Panel

- The device is either available as version for wall application or as version for ceiling application.
- The device is suitable for indoor and outdoor use. (Outdoor use only with appropriate cable fittings. Not included in delivery.)
- The coverage of the device depends on the ambient light level. Consider also the maximum mounting height of the device.
- For reliable planning use the Planning Software by Bosch for Fire Alarm Systems.
- Remind that current consumption differs:

	Operating Voltage	High power 1 Hz	High power 0.5 Hz	Low power 1 Hz	Low power 0.5 Hz
Coverage		7.5 m (135 m ³)		2.5 m (15 m ³) / 3 m (21 m ³)	
White flash	24 VDC	25 mA	16 mA	16 mA	10 mA
Red flash	24 VDC	25 mA	16 mA	16 mA	10 mA

Technical specifications

Mechanics

Housing and base color	Red similar to RAL 3031 White similar to RAL 9003
Weight	100 g

Electrical

Operating voltage	9 - 60 VDC
Current consumption	10 - 25 mA, dependent on flash rate setting and coverage setting
Monitoring	Reverse polarity

Environmental conditions

Protection class	IP33C shallow base / IP65 deep base *
Permissible operating temperature	-25°C - +70°C
Permissible rel. humidity	Complies with EN54-23 (93% ±3%)

*Manufacturers specification, not third party verified

Ceiling

Dimensions (Ø x H)	93 mm x 37 mm / 93 mm x 65 mm
Maximum mounting height (x)	3 m
Coverage (y)	7.5 m (switchable to 3 m)
Coverage volume	132 m ³ (21 m ³)
Coverage volume code (C-x-y)	C-3-7.5
Flash rate	1Hz (switchable to 0.5 Hz)
Flash color	White or red

Wall

Dimensions (Ø x H)	93 mm x 38 mm / 93 mm x 66 mm
Maximum mounting height (x)	2.4 m
Coverage (y)	7.5 m (switchable to 2.5 m)
Coverage volume	135 m ³ (15 m ³)
Coverage volume code (W-x-y)	W-2.4-7.5

Flash rate	1Hz (switchable to 0.5 Hz)
Flash color	White or red

Ordering information

SOL-LX-C-WF-W-S White-flash beacon ceiling, shallow
for local visual alarm notification
Order number **SOL-LX-C-WF-W-S**

SOL-LX-C-RF-W-S Red-flash beacon ceiling, shallow
for local visual alarm notification
Order number **SOL-LX-C-RF-W-S**

SOL-LX-C-WF-W-D White-flash beacon ceiling, deep
for local visual alarm notification
Order number **SOL-LX-C-WF-W-D**

SOL-LX-C-RF-W-D Red-flash beacon ceiling, deep
for local visual alarm notification
Order number **SOL-LX-C-RF-W-D**

SOL-LX-W-WF-W-S White-flash beacon wall, shallow, white
for local visual alarm notification
Order number **SOL-LX-W-WF-W-S**

SOL-LX-W-RF-W-S Red-flash beacon wall, shallow, white
for local visual alarm notification
Order number **SOL-LX-W-RF-W-S**

SOL-LX-W-WF-W-D White-flash beacon wall, deep, white
for local visual alarm notification
Order number **SOL-LX-W-WF-W-D**

SOL-LX-W-RF-W-D Red-flash beacon wall, deep, white
for local visual alarm notification
Order number **SOL-LX-W-RF-W-D**

SOL-LX-W-WF-R-S White-flash beacon wall, shallow, red
for local visual alarm notification
Order number **SOL-LX-W-WF-R-S**

SOL-LX-W-RF-R-S Red-flash beacon wall, shallow, red
for local visual alarm notification
Order number **SOL-LX-W-RF-R-S**

SOL-LX-W-WF-R-D White-flash beacon wall, deep, red
for local visual alarm notification
Order number **SOL-LX-W-WF-R-D**

SOL-LX-W-RF-R-D Red-flash beacon wall, deep, red
for local visual alarm notification
Order number **SOL-LX-W-RF-R-D**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
emea.securitysystems@bosch.com
emea.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Germany
www.boschsecurity.com

North America:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.us

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia