# Safety

#### Danger!





Injuries due to electricity are possible if the system is not operated correctly or if the system is opened or modified. Never open or modify the system. Contact your installer if you want to get your system modified.

#### Caution!



Sensitive components

Damage of sensitive components is possible if the system is not handled carefully or if the system is opened or modified.

- Always handle the system carefully.
- Never open or modify the system.
- Please contact your installer if you want to get your system modified.

### Old electrical and electronic equipment



This product and/or battery must be disposed of separately from household waste. Dispose such equipment according to local laws and regulations, to allow their reuse and/or recycling. This will help in conserving resources, and in protecting human health and the environment.


## **Short information**

This document provides a short description on the most important operations of the MAP 5000 system.

For detailed information and instructions on operation, refer to the MAP touch keypad 5000 User manual.

# System overview

Three light-emitting diodes (LEDs) are located on the left side of the MAP keypad housing:



Cal- lout	Compon- ent	Description
1	Green LED	Indicates that the keypad is in normal condition.
2	Yellow LED	Indicates that there is a trouble condition, that devices are covered, or that devices of the system are bypassed or disabled.
3	Red LED	The default behavior indicates that an alarm condition exists in the security system.

# **Operation**

### Logging in

#### How to log in

- To view the login screen, tap the screen.
- In the passcode field, enter your passcode. The user passcode is a combination of the 3-digit user ID and a 6-digit password (e.g. 005 123456).

If the passcode is correct, the Main Menu is displayed.

### Invalid passcode

If the passcode is not correct, an error message is displayed.

To empty the passcode field, press



When an incorrect passcode has been entered ten times, the keypad is locked for two minutes per default. These values can be configured by the installer via RPS for MAP.

#### Silencing alarms

# How to silence the acoustic alarm of the local keypad

- Touch the screen of the local keypad.
- The login screen is displayed and the acoustic alarm on the local keypad is silenced.

## How to silence all acoustic alarms of remote devices

- Log in to display all acoustic alarms. Refer to How to log in.
  - The first and last alarms are displayed immedi-
- To silence the alarms of all remote acoustic

devices and keypads, press

The alarms of all remote acoustic devices and keypads are silenced.

#### **Arming areas**

#### How to open the Arm menu







- The Arm menu with three menu options is dis-
- played.


#### How to arm

- Select one of the three menu options to proceed. The area and their current arming possibility are displayed.
- An area is ready to arm, if the played.



An area is not ready to arm, if the played.

### How to arm, if area is ready to arm



1. To arm an area that is ready to arm, press the desired option or area.



A countdown starts, indicating the remaining time to exit the location.

- 3. Exit the area within the remaining time of the countdown.
- $\Rightarrow$ The area is armed.

### How to make an area ready to arm

- An area is not ready to arm, if the displayed. There are active or faulted devices in
- To arm an area that is not ready to arm, press 1. the desired option or area.



All active or faulted devices, that either can be bypassed or cannot be bypassed, are displayed.

Resolve the issues of the listed devices to make this area ready to arm.

#### How to force arm

If you want to arm the area without the devices listed and if the preconditions are fulfilled, press Force Arm.

#### Disarming areas

#### How to open the Disarm menu

To open the **Disarm** menu, press



- The **Disarm** menu with three menu options is dis
  - played.

#### How to disarm

Select one of the three menu options to pro-

The area and their current arming status are displayed. An area is armed and can be disarmed if



icon is displayed.

To disarm an area, press the desired option or



2.

The area is disarmed.

## Viewing area status

played.

#### How to open the Status menu

To open the **Status** menu, press

The Status menu with four menu options is dis-

#### How to view the area status

Press View Area Status.

A list with all areas and their status is displayed.

symbol indicates that there is detailed information to be displayed for an area. You can also search for areas by name or filter areas according to their arming or disarming

To view details on the area status, press the



Details on the area status are displayed.

## Bypassing

# How to open the Status menu

To open the Status menu, press



The Status menu with four menu options is displayed.

### How to bypass or unbypass a device

Press Bypass/Unbypass Device.

A list with all devices that can be bypassed or unbypassed are displayed. You can also search for devices by name or filter devices according to their fault and bypass status.

- To change the status of a device, press the button of the device.
- ⇒ The icon indicates that the device is un-

bypassed. The icon and the yellow LED on the keypad indicate that the device is bypassed.

## Logging off

#### How to log off

To log off, press



# Troubleshooting

Please contact your installer in case of problems or any unexpected behavior of the system.

For detailed information and instructions on operation, refer to the MAP touch keypad 5000 User manual.


Scan the QR code to download the User manual.





# MAP touch keypad 5000

IUI-MAP0002-3



#### Bosch Sicherheitssysteme GmbH

Robert-Bosch-Platz 1 70839 Gerlingen Germany

### www.boschsecurity.com

© Bosch Sicherheitssysteme GmbH, 2024

Building solutions for a better life

06-2024 | V02 | F.01U.424.525 | 202409121150