

TINYON IP 2000 WI

www.boschsecurity.com



BOSCH
Invented for life



The 720p indoor microbox cameras with WiFi and a passive infrared (PIR) motion detector are ready-to-use, complete network video surveillance systems inside a compact and stylish housing. These cameras bring Bosch's high-performance technology into the realm of homes, small office and retail businesses by offering a cost-effective solution for a broad range of applications.

System overview

Ideal for indoor use, the compact, aesthetic design is suitable for installations where housing size and appearance are important. The camera is available in two colors and is supplied with a versatile mounting bracket, allowing it to be easily positioned for best coverage.

The wireless connectivity, with no external antenna, further enhances the aesthetic nature of the installation and also removes the need for a network cable.



- ▶ Compact and stylish 720p indoor wireless LAN camera
- ▶ IEEE 802.11b/g/n wireless connectivity
- ▶ WPS for easy wireless network setup
- ▶ Built-in PIR motion detector and white light illuminator
- ▶ FTP, Dropbox and e-mail alarms

Functions

Integrated wireless connection

The integrated wireless LAN feature supports the IEEE 802.11b, g and n standards allowing the camera to connect to fast WiFi access points. The WPS button provides an easy and simple way to set up the wireless LAN connection and security settings.

Motion and audio detection

The built-in passive infrared (PIR) sensor detects motion within 5 meters, even in complete darkness. It can then trigger an alarm, start recording or switch on the integrated white light LED to provide illumination in darkened rooms. These functions can also be activated by the detection of sound by the built-in microphone.

Built-in microphone and loudspeaker

The built-in microphone and loudspeaker allows remote users to listen in on an area and communicate messages to visitors or intruders via the loudspeaker. Audio detection can be used to generate an alarm if needed.

Intelligent Dynamic Noise Reduction

Quiet scenes with little or no movement require a lower bitrate. By intelligently distinguishing between noise and relevant information, Intelligent Dynamic Noise Reduction reduces bitrate by up to 50%.

Because noise is reduced at the source during image capture, the lower bitrate does not compromise on video quality.

With Intelligent Dynamic Noise Reduction, our focus is to significantly reduce storage costs, and lessen network strain by only using bandwidth when needed.

Area-based encoding

Area-based encoding is another feature which reduces bandwidth. Compression parameters for up to eight user-definable regions can be set. This allows uninteresting regions to be highly compressed, leaving more bandwidth for important parts of the scene.

Bitrate optimized profile

The average typical optimized bandwidth in kbits/s for various image rates is shown in the table:

fps	720p	480p
30	1200	600
15	955	478
12	877	438
5	568	284
2	245	122

Multiple streams

The innovative multi-streaming feature delivers various H.264 streams together with an M-JPEG stream. These streams facilitate bandwidth-efficient viewing and recording as well as integration with third-party video management systems.

Depending on the resolution and frame rate selected for the first stream, the second stream provides a copy of the first stream or a lower resolution stream.

The third stream uses the I-frames of the first stream for recording; the fourth stream shows a JPEG image at a maximum of 10 Mbit/s.

Easy installation

The power supply adapter delivered with the camera provides the +5 VDC power supply required. The wireless connectivity removes the need for a network cable, however, an Ethernet compliant network cable can be connected if required. The WPS button simplifies the selection of a WiFi network and the network password setting.

Tamper and motion detection

A wide range of configuration options is available for alarms signaling camera tampering. A built-in algorithm for detecting movement in the video can also be used for alarm signaling.

Cloud-based services

The camera supports time-based or alarm-based JPEG posting to four different accounts. These accounts can address FTP servers or cloud-based storage facilities (for example, Dropbox). Video clips or JPEG images can also be exported to these accounts.

Alarms can be set up to trigger an e-mail or SMS notification so you are always aware of abnormal events.

Access Security

Password protection with three levels and 802.1x authentication is supported. To secure Web browser access, use HTTPS with a SSL certificate stored in the camera.

Complete viewing software

There are many ways to access the camera's features: using a web browser, with the Bosch Video Management System, with the free-of-charge Bosch Video Client, with the video security mobile app, or via third-party software.

Video security App

The Bosch video security mobile App has been developed to enable **Anywhere** access to HD surveillance images allowing you to view live images from any location. The App is designed to give you complete control of all your cameras, from panning and tilting to zoom and focus functions. It's like taking your control room with you.

This App, together with the separately available Bosch transcoder, will allow you to fully utilize our dynamic transcoding features so you can play back images even over low-bandwidth connections.

System integration

The camera conforms to the ONVIF Profile S specification. Compliance with this standard guarantees interoperability between network video products regardless of manufacturer.

Third-party integrators can easily access the internal feature set of the camera for integration into large projects. Visit the Bosch Integration Partner Program (IPP) website (ipp.boschsecurity.com) for more information.

Certifications and approvals

HD standards

Complies with the SMPTE 296M-2001 Standard in:

- Resolution: 1280x720
- Scan: Progressive
- Color representation: complies with ITU-R BT.709
- Aspect ratio: 16:9
- Frame rate: 25 and 30 frames/s

Standards	
	EN 60950-1; UL 60950-1; CAN/CSA-C22.2 NO. 60950-1-07
	FCC Part15 Subpart B, Class B

	FCC Part15 Subpart C
	EMC directive 2004/108/EC
	EMC directive 1999/5/EC
	EN 300 328
	EN 301 489-1-17
	EN 62311
	EN 50130-4
	EN 50130-5
	EN 55022 class B
	EN 55024
	EN 61000-3-2
	EN 61000-3-3
	SRRC China
ONVIF conformance	EN 50132-5-2; IEC 62676-2-3
Product certifications	CE, FCC, UL, cUL, CB

Region	Certification
Europe	CE
USA	UL

Installation/configuration notes

Parts included

	Item
1x	TINYON camera
1x	Power adapter
1x	Mounting bracket
2x	Mounting screws with wall plugs
1x	Quick Install Guide
1x	Identification label sheet

Technical specifications

Power	
Power Supply	+5 VDC via supplied power adapter
Power Consumption	4.4 W typical
Power adapter	100-240 VAC to +5 VDC power supply included

Sensor	
Type	1/4-inch CMOS
Total sensor pixels	1280 x 800 (1MP)

Video performance – Sensitivity (3200K, 89% reflectivity, 30IRE, F2.8)	
Sensitivity	1.0 lx 0.0 lx (with LED)

Video performance - Dynamic range	
Dynamic range	76 dB

Video streaming	
Video compression	H.264 (MP); M- JPEG
Streaming	Multiple configurable streams in H.264 and M-JPEG, configurable frame rate and bandwidth.
Overall IP Delay	Min. 120 ms, Max. 340 ms
GOP structure	IP, IBP, IBBP
Encoding interval	1 to 30 ips

Video resolution (H x V)	
720p HD	1280 x 720 (at 30 ips)
Upright 9:16 (cropped)	400 x 720
D1 4:3 (downscaled/cropped)	704 x 480
480p SD	Encoding: 704 x 480; Displayed: 854 x 480
432p SD	768 x 432
288p SD	512 x 288
240p SD	Encoding: 352 x 240; Displayed: 432 x 240
144p SD	256 x 144

Video functions	
Adjustable picture settings	Contrast, Saturation, Brightness
White Balance	Standard automatic mode, manual mode and hold
Shutter	Automatic Electronic Shutter (1/30 to 1/150000) Fixed shutter (1/30 to 1/15000) selectable
Backlight compensation	On/off
Noise reduction	Intelligent Dynamic Noise Reduction
Privacy Masking	Four independent areas, fully programmable

Video functions	
Video Analysis	MOTION+
Other functions	Image mirror, Image flip, Pixel counter, Video watermarking, Display stamping, Motion detection, Tamper alarm, Audio alarm
Audio streaming	
Standard	G.711, 8 kHz sampling rate L16, 16 kHz sampling rate AAC-LC, 48 kbps at 16 kHz sampling rate AAC-LC, 80 kbps at 16 kHz sampling rate
Signal-to-Noise Ratio	>50 dB
Audio Streaming	Full-duplex / half duplex
Input/output	
Audio input	Built-in microphone
Audio output	Built-in loudspeaker
Alarm input	1 input
Alarm activation voltage	0 to 3.3 VDC active low, or short
Alarm output	1 output
Alarm output voltage	+5 VDC Load current 1 A max.
Detection	
Detector	PIR (passive infrared)
Distance	5 m (16 ft)
Detection angle	90° (H)
Night vision	
Distance	4 m (13 ft)
Illumination	White light LED
Optical	
Lens type	Fixed 2.5 mm, F2.8
Lens mount	Board mounted
Horizontal field of view	89°
Vertical field of view	50°
Software	
Unit Configuration	Via web browser or Configuration Manager
Firmware update	Remotely programmable
Software viewer	Web browser, Bosch Video Client, or third party software

Wireless LAN	
Wireless standard	IEEE 802.11b/g/n
Wireless security	WPA-PSK (TKIP), WPA2-PSK (AES)
WiFi protected setup	WPS button, PIN
Network	
Protocols	IPv4, IPv6, UDP, TCP, HTTP, HTTPS, RTP/RTCP, IGMP V2/V3, ICMP, ICMPv6, RTSP, FTP, Telnet, ARP, DHCP, APIPA (Auto-IP, link local address), NTP (SNTP), SNMP (V1, MIB-II), 802.1x, DNS, DNSv6, DDNS (DynDNS.org, selfHOST.de, no-ip.com), SMTP, iSCSI, UPnP (SSDP), DiffServ (QoS), LLDP, SOAP, Dropbox, CHAP, digest authentication
Encryption	TLS 1.0, SSL, DES, 3DES
Ethernet	10/100 Base-T, auto-sensing, half/full duplex
Connectivity	ONVIF Profile S, Auto-MDIX
Mechanical	
Dimensions (H x W x D)	109 x 65 x 47 mm (4.29 x 2.56 x 1.85 in)
Weight	105 g (3.70 oz)
Environmental	
Operating Temperature	-10 °C to +40 °C (14 °F to +104 °F)
Storage Temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Humidity	0% to 95% relative humidity (non condensing)
Ordering information	
TINYON IP 2000 WI Cost-effective, ready-to-use, wireless LAN microbox camera with PIR for indoor surveillance. 720p30; 2.5 mm lens; +5 VDC PSU; motion/audio detection; cloud services; free viewing Apps; IDNR; PIR; wireless LAN; black Order number NPC-20012-F2WL	
TINYON IP 2000 WI Cost-effective, ready-to-use, wireless LAN microbox camera with PIR for indoor surveillance. 720p30; 2.5 mm lens; +5 VDC PSU; motion/audio detection; cloud services; free viewing Apps; IDNR; PIR; wireless LAN; white Order number NPC-20012-F2WL-W	
Accessories	
NPD-5001-POE Midspan PoE Injector Power-over-Ethernet midspan injector for use with PoE enabled cameras; 15.4 W, 1-port Order number NPD-5001-POE	

NPD-5004-POE Midspan PoE Injector

Power-over-Ethernet midspan injectors for use with PoE enabled cameras; 15.4 W, 4-ports
Order number **NPD-5004-POE**

Represented by:

North America:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
203 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

Latin America and Caribbean:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com