

# PVA-4R24 Router

www.boschsecurity.com



**BOSCH**  
Invented for life



- ▶ Expansion of PAVIRO system by 24 zones
- ▶ Total 4000 W speaker load, max 500W per zone
- ▶ 20 GPI, 24 GPO and 2 control relays
- ▶ Up to 20 routers per controller
- ▶ EN 54-16 and ISO 7240-16 system certification


The PVA-4R24 24 Zone Router is a zone extension for the PAVIRO system. It adds 24 zones, 20 GPIs, 24 GPOs and 2 control relays to the system and is controlled and supervised via the CAN bus by the PVA-4CR12 (Controller).

Up to 20 routers can be connected to one controller. One router can handle up to 4000 W speaker load. The maximum load of one zone is 500 W.

The zone indicator lights on the front indicate the current status of every zone:


- Green: Zone in use for non emergency purpose
- Red: Zone in use for emergency purpose
- Yellow: Zone fault detected
- Off: Zone in idle condition

## System overview



- 1 Zone status indicator light
- 2 Combined fault warning indicator light
- 3 Recessed button

- 4 Network indicator light
- 5 Standby indicator light
- 6 Power indicator light



- 1 Grounding screw
- 2 CONTROL IN ports
- 3 CONTROL OUT ports
- 4 AMP IN ports
- 5 SPEAKER OUT ports
- 6 DC power input
- 7 CAN ADDRESS selector switch
- 8 CAN BUS port

## Certifications and approvals

### Emergency standard certifications

Europe	EN 54-16
International	ISO 7240-16

### Environmental directive compliance

Safety	EN 60065
Immunity	EN 50130-4
Emissions	EN 61000-6-3 ICES-003 FCC-47 part 15B class A
Environment	EN 50581
Maritime	EN 60945

### Conformity

Europe	CE/CPR
USA	FCC
Canada	ICES
Australia	RCM
Korea	KCC
Russian Federation	EAC
Environment	RoHS

## Parts included

Quantity	Component
1	PVA-4R24 Router
1	Set of connectors
1	Set of feet
1	Installation manual
1	Important safety instructions

## Technical specifications

### Electrical

Audio inputs (100 V)	AMP IN: 4 x 6-pin port
• Max. voltage	120 V <sub>eff</sub>
• Max. current	7.2 A
• Max. power	500 W
Audio outputs (100 V)	SPEAKER OUT: 4 x 12-pin port
• Max. voltage	120 V <sub>eff</sub>
• Max. current	7.2 A

• Max. power	500 W
CONTROL IN	4 x 10-pin port
• Control inputs	<ul style="list-style-type: none"> <li>• 10 supervised inputs (0-24 V, U<sub>max</sub> = 32 V)</li> <li>• 10 isolated inputs (Low: U ≤ 5 V DC; High: U ≥ 10 V DC, U<sub>max</sub> = 32 V)</li> </ul>
CONTROL OUT	4 x 10-pin port
• Control outputs	24 Low Power outputs (open collector, U <sub>max</sub> = 32 V, I <sub>max</sub> = 40 mA)
• Control relay	2 (NO/NC relay contacts, U <sub>max</sub> = 32 V, I <sub>max</sub> = 1 A)
Interfaces	
• CAN BUS port	2 x RJ-45, 10 to 500 kbit/s (for controller, router, amplifier connection)
DC power input	21-32 V DC
Power consumption	5-60W
Maximum supply current (24 V)	
• Standby	• < 250 mA
• Idle/announcement/alert	• < 800 mA

### Environmental

Operating temperature	-5 °C to +45 °C (+23 °F to +113 °F)
Storage temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Humidity (non-condensing)	5% to 90%
Altitude	Up to 2000 m

### Mechanical

Dimensions (HxWxD)	88 mm x 483 mm x 391 mm
Weight (net)	8.2 kg
Mouting	Standalone; 19 in. rack
Color	Black with silver

## Ordering information

### PVA-4R24 Router

24-zone expansion unit for PAVIRO system, 2 RU  
Order number **PVA-4R24**

### Services

**EWE-PVORTR-IW 12mths wrty ext. PAVIRO Router**  
12 months warranty extension  
Order number **EWE-PVORTR-IW**

**Represented by:**

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
emea.securitysystems@bosch.com  
emea.boschsecurity.com

**Germany:**  
Bosch Sicherheitssysteme GmbH  
Robert-Bosch-Ring 5  
85630 Grasbrunn  
Germany  
www.boschsecurity.com

**North America:**  
Bosch Security Systems, LLC  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
onlinehelp@us.bosch.com  
www.boschsecurity.us

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia