

ET80 Multi-candela, Wall-mount, Vandal-resistant Speaker Strobes

www.boschsecurity.com



BOSCH
Invented for life



- ▶ 25 VRMS or 70 VRMS operation up to 8 W
- ▶ Low average current draw
- ▶ Extra protection and improved audibility through sealed-back speaker construction and vandal-resistant grill
- ▶ Compatible with SM and DSM Synchronization Modules
- ▶ Easy wiring with screw terminals

The Wheelock ET80 Multi-candela Speaker Strobes meet the critical needs of the life safety industry for voice and tone signaling. They have a vandal-resistant die-cast grill, a sealed-back speaker, and a Lexan lens for extra protection.

The high-efficiency speaker is designed for maximum output at a minimum wattage across a frequency range of 400 Hz to 4 kHz and covers both 25 V and 75 V audio systems with a series of wattage taps from 0.125 W to 8 W.

When used with the SM (single) or DSM (dual) Synchronization Modules, the strobe produces a synchronized strobe flash for compliance with ADA guidelines concerning photosensitive epilepsy. All strobe input is compatible with standard reverse polarity type supervision of circuit wiring by a fire alarm control panel (FACP).

Certifications and approvals

Cooper Wheelock, Inc. holds these Listings and Approvals:

Region	Certification	
USA	UL	UUKC: Signaling Appliances and Equipment for the Hearing Impaired (UL1971), UUMW: Speakers and Amplifiers for Fire Protective Signaling Systems (UL1480, UL1711, and UL2043)
	CSFM	see our website

Installation/configuration notes

Compatible Products

The following products are compatible with the ET80 Speaker Strobes:

Category	Product ID	Product Description
Control Panels	D7022 ¹	Conventional FACP
	D7024 ²	Addressable FACP
	D7024	Conventional FACP
	D8024 ¹	Analog FACP
	D9124 ¹	Addressable FACP
	D10024A ¹	Analog FACP
	FPA-1000	Analog Addressable FACP

	FPD-7024 ²	Addressable FACP
	FPD-7024	Conventional FACP
Modules	SM-12/24-R	Synchronization module (red)
	DSM-12/24-R	Dual synchronization module (red)

These speakers are compatible with Wheelock SAFEPATH4 Facility Communication Systems and Bosch Voice Evacuation Systems.

¹ For synchronization, use the SM or DSM modules with these control panels. The synchronization module must be set for 24 V operation. When used, the D7022 must be set for 24 VDC operation.

² When used with a D7039 Multiplex Expansion Module, the D7024 and FPD-7024 become addressable fire alarm control panels (FACPs).

Mounting

These speaker strobes mount on the indicated back boxes for the indicated applications:

	Conduit Applications	Surface Mounted	Flush Mounted
Four-inch square*			•
SBB Back Box	•	•	

* Requires an SER extension ring.

Wiring

Notice

Do not use the strobe unit in coded or pulsed signaling circuits.

The input terminals accept wires with diameters between 18 AWG and 12 AWG (ISO 0.75 mm² and 4 mm²).

Parts included

Quant.	Component
1	Speaker Strobe
1	Hardware pack
1	Literature pack

Technical specifications

Electrical

Strobe Current (RMS)

VDC: 15 cd: 6 mA, 30 cd: 9.2 mA, 75 cd: 16.5 mA, 110 cd: 22 mA

VFWR: 15 cd: 10.2 mA, 30 cd: 15.5 mA, 75 cd: 25.3 mA, 110 cd: 34.7 mA

Voltage (Input)

Nominal: 24 VDC

Range: 16 VDC or FWR to 33 VDC or FWR

Environmental

Relative Humidity: Up to 85%, non-condensing

Temperature (Operating): +32°F to +120°F (0°C to +49°C)

Mechanical

Dimensions: 5.4375 in. square x 5.6875 in. deep¹ (13.8 cm square x 14.4 cm deep¹)

Material: Molded plastic enclosure incorporating a Xenon flashtube and Lexan lens.

Candela Rating: 15 cd, 30 cd, 75 cd, or 110 cd

¹ When used in flush-mount installations, the unit extends 3.4375 in. (8.7 cm) from the mounting surface.

Speaker dB at 10 ft (3 m)

1/8 W	78 dB
1/4 W	81 dB
1/2 W	84 dB
1 W	87 dB
2 W	90 dB
4 W	92 dB
8 W	94 dB

Trademarks

All hardware and software product names used in this document are likely to be registered trademarks and must be treated accordingly.

Ordering information

ET80-24MCW-FR Vandal-Resistant Speaker Strobe (red)

Red, vandal-resistant, 24 VDC device providing high audio output with clear audibility, dual voltage capability (25 VRMS or 70 VRMS), field-selectable taps from 1/8 W to 8 W, and strobe intensities of 15 cd, 30 cd, 75 cd, or 110 cd

Order number **ET80-24MCW-FR**

ET80-24MCW-FW Vandal-Resistant Speaker Strobe (white)

White, vandal-resistant, 24 VDC device providing high audio output with clear audibility, dual voltage capability (25 VRMS or 70 VRMS), field-selectable taps from 1/8 W to 8 W, and strobe intensities of 15 cd, 30 cd, 75 cd, or 110 cd

Order number **ET80-24MCW-FW**

Represented by:

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com