

LBB 4560/xx Charging Units

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Can accommodate 56 pocket receivers
- ▶ Universal mains power facility allows use worldwide
- ▶ Rapid recharging: within 1 hour and 45 minutes

The charging units are used for charging and storing the INT-RXxx Pocket Receivers.

Functions

Controls and Indicators

- On/off switch
- Charging status indication on the pocket receivers

Interconnection

- Mains input with loop-through facility; male and female Euro mains socket
- 56 charging contacts. Compatible with INT-RXxx pocket receivers

Technical specifications

Electrical

Mains voltage	100-240 Vac, 50-60 Hz
Power consumption	300 W (56 receivers charging)
Power consumption (standby)	17 W (no receivers in the charging unit)

Mechanical

Mounting	
LBB 4560/50	Screws and plugs for wall mounting included
Dimensions (H x W x D)	
LBB 4560/00	230 x 690 x 530 mm (9 x 27 x 21 in)
LBB 4560/50	130 x 680 x 520 mm (5 x 27 x 20 in)
Weight excl. receivers	
LBB 4560/00	15.5 kg (34 lb)
LBB 4560/50	11.2 kg (25 lb)
Weight incl. 56 receivers	
LBB 4560/00	22.3 kg (49 lb)
LBB 4560/50	18.0 kg (40 lb)
Color	Charcoal with grey

Ordering information

LBB4560/00 Charger case for 56x LBB4540

Integrus charging case for pocket receivers, for portable use.

Order number **LBB4560/00**

LBB4560/50 Charger cabinet for 56x LBB4540

Integrus charging cabinet for pocket receivers, for fixed installation.

Order number **LBB4560/50**

LBB4560/00-JP Charger case for 56x LBB4540

Integrus charging case for pocket receivers, for portable use. Japanese version.

Order number **LBB4560/00-JP**

LBB4560/50-JP Charger cabinet for 56x LBB4540

Integrus charging cabinet for pocket receivers, for fixed installation. Japanese version.

Order number **LBB4560/50-JP**

LBB4560/00-US Charger case for 56x LBB4540

Integrus charging case for pocket receivers, for portable use. US version.

Order number **LBB4560/00-US**

LBB4560/50-US Charger cabinet for 56x LBB4540

Integrus charging cabinet for pocket receivers, for fixed installation. US version.

Order number **LBB4560/50-US**

Represented by:

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: + 31 40 2577 284
emea.securitysystems@bosch.com
emea.boschsecurity.com

Germany:
Bosch Sicherheitssysteme GmbH
Robert-Bosch-Ring 5
85630 Grasbrunn
Germany
www.boschsecurity.com

North America:
Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
onlinehelp@us.bosch.com
www.boschsecurity.us

Asia-Pacific:
Robert Bosch (SEA) Pte Ltd, Security Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia