

# wLSN Diversity Hub

www.boschsecurity.com



**BOSCH**  
Invented for life



The wLSN Diversity Hub acts as the link between wireless Local Security Network (wLSN) devices and compatible controls panels. The wLSN Diversity Hub is the functional center of the wLSN system and is responsible for coordinating all network activity. The wLSN Diversity Hub communicates with the compatible control panels through a four-wire Option Bus interface, and acts as the network master for the wLSN system. As the network master, the wLSN Diversity Hub provides network timing and synchronization, monitors sensor nodes and network status, and sends configuration data to the sensor nodes as required.

## Certifications and approvals

Designed to comply with AFNOR (NF-A2P)

- ▶ Multiple internal antennas provide spatial diversity for improved RF signal quality in both transmit and receive modes
- ▶ Provides control of the wLSN system through an integrated base station transceiver module
- ▶ Provides two-way communication with compatible control panels through a four-wire Option Bus interface
- ▶ Manages a non-volatile database of status and configuration information for all sensor nodes in the network
- ▶ Supervised for cover and wall tamper conditions

Region	Certification	
Europe	CE	2004/108/EC EMC Directive; 2006/95/EC LVD Directive; 1999/5/EC R&TTE Directive; EN 50130-4 1996, +A1 & A2; EN 55022 2006; EN 60950-1 2006; EN 300 220-1 V2.1.1:2006; EN 301 489-1 V1.8.1:2008
Belgium	INCERT	B-509-0054d

## Installation/configuration notes

### Compatibility Information

All wireless Local Security Network (wLSN) devices including the wLSN Diversity Hub are compatible with the Easy Series Control Panel.

### Mounting Considerations

Mount the Hub on an interior wall or ceiling where it is protected from weather elements such as rain or snow, in a location that appears suitable for RF performance, and where it can be conveniently wired to the control panel.

**Notice**

Installation on metal surfaces can affect the RF propagation pattern of the radio transceiver.

The RF transceiver has a range of approximately 1000 m (3000 ft) in open air.

**Parts included**

Quantity	Component
1	wLSN Diversity Hub (ISW-BHB2-WX)
1	Hardware Kit (includes stainless steel screws, wall anchor, and cable tie)
1	Literature Pack <ul style="list-style-type: none"> <li>• Installation Guide</li> <li>• Reference Guide</li> </ul>

**Technical specifications****Environmental Considerations**

Environment:	Indoor, dry
Relative Humidity:	Up to 95%, non-condensing
Temperature (operating):	-10°C to +55°C (+14°F to +131°F)
EN50130-5:	Environmental Class II

**Mechanical Properties**

Color:	Off-white
Dimensions (H x W x D):	14.0 cm x 19.0 cm x 3.8 cm (5.5 in. x 7.5 in. X 1.5 in.)

**Power Requirements**

Voltage (supply):	12 VDC nominal from control panel, 7 VDC to 14 VDC acceptable range
Current Requirement:	60 mA over entire voltage range

**Transmission and Reception Characteristics**

Frequency:	European Security Band 868 MHz to 869 MHz
Range (open field):	1000 m (3000 ft)

**Trademarks**

Trademark names are used throughout this document. In most cases, these designations are claimed as trademarks or registered trademarks in one or more countries by their respective owners. Rather than placing a trademark symbol in every occurrence of a trademark name, Bosch Security Systems, Inc. uses the names only in an editorial fashion and to the benefit of the trademark owner with no intention of infringing the trademark.

**Ordering information****wLSN Diversity Hub**

Coordinates all network activity in a wireless Local Security Network (wLSN) system.

Order number **ISW-BHB2-WX**

**Represented by:**

**Americas:**

Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**

Bosch Security Systems B.V.  
P.O. Box 80002  
5617 BA Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**

Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia

**China:**

Bosch (Shanghai) Security Systems Ltd.  
201 Building, No. 333 Fuquan Road  
North IBP  
Changning District, Shanghai  
200335 China  
Phone +86 21 22181111  
Fax: +86 21 22182398  
www.boschsecurity.com.cn

**America Latina:**

Robert Bosch Ltda Security Systems Division  
Via Anhanguera, Km 98  
CEP 13065-900  
Campinas, Sao Paulo, Brazil  
Phone: +55 19 2103 2860  
Fax: +55 19 2103 2862  
latam.boschsecurity@bosch.com  
www.boschsecurity.com